





外輪	POM
軸承	鋼

圖 7

圖 8



品號	備註	D 0 -0.1	W 0 -0.2	C ±0.4	L ±0.5	N	荷重 (N)	庫存						
K-DR-19-B1-5.5	圖7	19	6	1	5.5	8.2	49	.						
K-DR-19-B1				8										
K-DR-19-B2-4.5				2	4.5									
K-DR-19-B2				2.7	8									
K-DR-19-B2.7														
K-DR-19-B3				3										
K-DR-22-B1				圖7	22				7	1	5.5	9.5	196	.
K-DR-22-B2-5.5										2	8			
K-DR-22-B2										3	4.5			
K-DR-22-B3										4	8			
K-DR-22-B4-4.5														
K-DR-22-B4										5				
K-DR-22-B5										6				
K-DR-22-B6										24	7			
K-DR-24-B2	3													
K-DR-24-B3	4													
K-DR-24-B4	5													
K-DR-24-B5	6													
K-DR-24-B6	26	7	2			6	9.5	196						
K-DR-26-B2			3											
K-DR-26-B3			4											
K-DR-26-B4			6	8										
K-DR-26-B6-6														
K-DR-26-B6	28	7	2	11	13.0	196	.							
K-DR-28-B2			3											
K-DR-28-B3			2					11						
K-DR-22-BH2-11														
K-DR-22-BH3-11	26	7	2	11	13.0	196	.							
K-DR-26-BH2-11														
K-DR-28-BH2-11	28													

Ps) 備註

- 溫度範圍：0°C~40°C
- 滾輪請勿施予軸向荷重
- 容許荷重是本公司300RPM/100萬回的測試值
- 1N=0.101972kgf

Wa) 注意

· 非庫存品必須以101pcs為單位購買之

訂貨： 交期： 天 庫存
K-DR-19-B1 其它