



底座		螺栓		防滑墊	
材質	顏色	材質	材質	硬度	
PA+玻纖	藍	SUS304	NBR	蕭氏A70	

品號	描述	D	d	L	L1	l	l1	h	s	螺栓球頭 (ø)	最大靜態荷重 (N)	質量 g	庫存
188101	LS.A-25-14-AS-SST-M8x43-VD	25	M8	67	70	43	24	12	14	14	7000	35	△
188103	LS.A-25-14-AS-SST-M8x68-VD	25	M8	92	95	68	24	12	14	14	7000	45	△
188111	LS.A-25-14-AS-SST-M10x43-VD	25	M10	67	70	43	24	12	14	14	7000	45	△
188113	LS.A-25-14-AS-SST-M10x68-VD	25	M10	92	95	68	24	12	14	14	7000	58	△
188115	LS.A-25-14-AS-SST-M10x98-VD	25	M10	122	125	98	24	12	14	14	7000	72	△
188121	LS.A-25-14-AS-SST-M12x43-VD	25	M12	67	70	43	24	12	14	14	7000	55	△
188123	LS.A-25-14-AS-SST-M12x68-VD	25	M12	92	95	68	24	12	14	14	7000	73	△
188125	LS.A-25-14-AS-SST-M12x98-VD	25	M12	122	125	98	24	12	14	14	7000	95	△
188131	LS.A-25-14-AS-SST-M14x68-VD	25	M14	92	95	68	24	12	14	14	7000	88	△
188133	LS.A-25-14-AS-SST-M14x98-VD	25	M14	122	125	98	24	12	14	14	7000	109	△
188135	LS.A-25-14-AS-SST-M14x148-VD	25	M14	172	175	148	24	12	14	14	7000	192	△
188141	LS.A-25-14-AS-SST-M16x68-VD	25	M16	92	95	68	24	12	16	14	7000	118	△
188143	LS.A-25-14-AS-SST-M16x108-VD	25	M16	132	135	108	24	12	16	14	7000	169	△
188145	LS.A-25-14-AS-SST-M16x148-VD	25	M16	172	175	148	24	12	16	14	7000	222	△
188147	LS.A-25-14-AS-SST-M16x168-VD	25	M16	192	195	168	24	12	16	14	7000	249	△
188201	LS.A-32-14-AS-SST-M8x43-VD	32	M8	68	71	43	25	15	14	14	9000	42	△
188203	LS.A-32-14-AS-SST-M8x68-VD	32	M8	93	96	68	25	15	14	14	9000	52	△
188211	LS.A-32-14-AS-SST-M10x43-VD	32	M10	68	71	43	25	15	14	14	9000	52	△
188213	LS.A-32-14-AS-SST-M10x68-VD	32	M10	93	96	68	25	15	14	14	9000	65	△
188215	LS.A-32-14-AS-SST-M10x98-VD	32	M10	123	126	98	25	15	14	14	9000	79	△
188221	LS.A-32-14-AS-SST-M12x43-VD	32	M12	68	71	43	25	15	14	14	9000	62	△
188223	LS.A-32-14-AS-SST-M12x68-VD	32	M12	93	96	68	25	15	14	14	9000	82	△
188225	LS.A-32-14-AS-SST-M12x98-VD	32	M12	123	126	98	25	15	14	14	9000	102	△
188231	LS.A-32-14-AS-SST-M14x68-VD	32	M14	93	96	68	25	15	14	14	9000	99	△
188233	LS.A-32-14-AS-SST-M14x98-VD	32	M14	123	126	98	25	15	14	14	9000	120	△
188235	LS.A-32-14-AS-SST-M14x148-VD	32	M14	173	176	148	25	15	14	14	9000	203	△
188241	LS.A-32-14-AS-SST-M16x68-VD	32	M16	93	97	68	25	15	16	14	9000	125	△
188243	LS.A-32-14-AS-SST-M16x108-VD	32	M16	133	137	108	25	15	16	14	9000	179	△
188245	LS.A-32-14-AS-SST-M16x148-VD	32	M16	173	176	148	25	15	16	14	9000	232	△
188247	LS.A-32-14-AS-SST-M16x168-VD	32	M16	193	196	168	25	15	16	14	9000	259	△
188301	LS.A-40-14-AS-SST-M8x43-VD	40	M8	68	71	43	25	17	14	14	13000	49	△
188303	LS.A-40-14-AS-SST-M8x68-VD	40	M8	93	96	68	25	17	14	14	13000	59	△
188311	LS.A-40-14-AS-SST-M10x43-VD	40	M10	68	71	43	25	17	14	14	13000	59	△
188313	LS.A-40-14-AS-SST-M10x68-VD	40	M10	93	96	68	25	17	14	14	13000	72	△
188315	LS.A-40-14-AS-SST-M10x98-VD	40	M10	123	126	98	25	17	14	14	13000	86	△
188321	LS.A-40-14-AS-SST-M12x43-VD	40	M12	68	71	43	25	17	14	14	13000	69	△
188323	LS.A-40-14-AS-SST-M12x68-VD	40	M12	93	96	68	25	17	14	14	13000	87	△
188325	LS.A-40-14-AS-SST-M12x98-VD	40	M12	123	126	98	25	17	14	14	13000	109	△
188331	LS.A-40-14-AS-SST-M14x68-VD	40	M14	93	96	68	25	17	14	14	13000	102	△

品號	描述	D	d	L	L1	l	l1	h	s	螺栓球頭 (ø)	最大靜態荷重 (N)	質量 g	庫存
188333	LS.A-40-14-AS-SST-M14x98-VD	40	M14	123	126	98	25	17	14	14	13000	123	△
188335	LS.A-40-14-AS-SST-M14x148-VD	40	M14	173	176	148	25	17	14	14	13000	206	△
188341	LS.A-40-14-AS-SST-M16x68-VD	40	M16	93	96	68	25	17	16	14	13000	132	△
188343	LS.A-40-14-AS-SST-M16x108-VD	40	M16	133	136	108	25	17	16	14	13000	186	△
188345	LS.A-40-14-AS-SST-M16x148-VD	40	M16	173	176	148	25	17	16	14	13000	239	△
188347	LS.A-40-14-AS-SST-M16x168-VD	40	M16	193	196	168	25	17	16	14	13000	266	△
188401	LS.A-50-14-AS-SST-M8x43-VD	50	M8	70	73	43	27	19	14	14	13000	61	△
188403	LS.A-50-14-AS-SST-M8x68-VD	50	M8	95	98	68	27	19	14	14	13000	71	△
188411	LS.A-50-14-AS-SST-M10x43-VD	50	M10	70	73	43	27	19	14	14	13000	71	△
188413	LS.A-50-14-AS-SST-M10x68-VD	50	M10	95	98	68	27	19	14	14	13000	84	△
188415	LS.A-50-14-AS-SST-M10x98-VD	50	M10	125	128	98	27	19	14	14	13000	98	△
188421	LS.A-50-14-AS-SST-M12x43-VD	50	M12	70	73	43	27	19	14	14	13000	81	△
188423	LS.A-50-14-AS-SST-M12x68-VD	50	M12	95	98	68	27	19	14	14	13000	99	△
188425	LS.A-50-14-AS-SST-M12x98-VD	50	M12	125	128	98	27	19	14	14	13000	121	△
188431	LS.A-50-14-AS-SST-M14x68-VD	50	M14	95	98	68	27	19	14	14	13000	114	△
188433	LS.A-50-14-AS-SST-M14x98-VD	50	M14	125	128	98	27	19	14	14	13000	135	△
188435	LS.A-50-14-AS-SST-M14x148-VD	50	M14	175	178	148	27	19	14	14	13000	218	△
188441	LS.A-50-14-AS-SST-M16x68-VD	50	M16	95	98	68	27	19	16	14	13000	144	△
188443	LS.A-50-14-AS-SST-M16x108-VD	50	M16	135	138	108	27	19	16	14	13000	197	△
188445	LS.A-50-14-AS-SST-M16x148-VD	50	M16	175	178	148	27	19	16	14	13000	251	△
188447	LS.A-50-14-AS-SST-M16x168-VD	50	M16	195	198	168	27	19	16	14	13000	278	△
188501	LS.A-60-14-AS-SST-M8x43-VD	60	M8	76	79	43	33	24	14	14	14000	81	△
188503	LS.A-60-14-AS-SST-M8x68-VD	60	M8	101	104	68	33	24	14	14	14000	93	△
188511	LS.A-60-14-AS-SST-M10x43-VD	60	M10	76	79	43	33	24	14	14	14000	90	△
188513	LS.A-60-14-AS-SST-M10x68-VD	60	M10	101	104	68	33	24	14	14	14000	103	△
188515	LS.A-60-14-AS-SST-M10x98-VD	60	M10	131	134	98	33	24	14	14	14000	117	△
188521	LS.A-60-14-AS-SST-M12x43-VD	60	M12	76	79	43	33	24	14	14	14000	100	△
188523	LS.A-60-14-AS-SST-M12x68-VD	60	M12	101	104	68	33	24	14	14	14000	118	△
188525	LS.A-60-14-AS-SST-M12x98-VD	60	M12	131	134	98	33	24	14	14	14000	140	△
188531	LS.A-60-14-AS-SST-M14x68-VD	60	M14	101	104	68	33	24	14	14	14000	141	△
188533	LS.A-60-14-AS-SST-M14x98-VD	60	M14	131	134	98	33	24	14	14	14000	162	△
188535	LS.A-60-14-AS-SST-M14x148-VD	60	M14	181	184	148	33	24	14	14	14000	245	△
188541	LS.A-60-14-AS-SST-M16x68-VD	60	M16	101	104	68	33	24	16	14	14000	163	△
188543	LS.A-60-14-AS-SST-M16x108-VD	60	M16	141	144	108	33	24	16	14	14000	217	△
188545	LS.A-60-14-AS-SST-M16x148-VD	60	M16	181	184	148	33	24	16	14	14000	270	△
188547	LS.A-60-14-AS-SST-M16x168-VD	60	M16	201	204	168	33	24	16	14	14000	297	△
188551	LS.A-60-24-AS-SST-M16x58-VD	60	M16	101	104	58	43	24	24	24	18000	226	△
188553	LS.A-60-24-AS-SST-M16x98-VD	60	M16	141	144	98	43	24	24	24	18000	279	△
188555	LS.A-60-24-AS-SST-M16x138-VD	60	M16	181	184	138	43	24	24	24	18000	330	△
188557	LS.A-60-24-AS-SST-M16x158-VD	60	M16	201	204	158	43	24	24	24	18000	358	△
188561	LS.A-60-24-AS-SST-M20x98-VD	60	M20	141	144	98	43	24	24	24	18000	351	△
188563	LS.A-60-24-AS-SST-M20x138-VD	60	M20	181	184	138	43	24	24	24	18000	432	△
188565	LS.A-60-24-AS-SST-M20x158-VD	60	M20	201	204	158	43	24	24	24	18000	472	△
188567	LS.A-60-24-AS-SST-M20x198-VD	60	M20	241	244	198	43	24	24	24	18000	558	△
188571	LS.A-60-24-AS-SST-M24x98-VD	60	M24	141	144	98	43	24	24	24	18000	452	△
188573	LS.A-60-24-AS-SST-M24x158-VD	60	M24	201	204	158	43	24	24	24	18000	629	△
188575	LS.A-60-24-AS-SST-M24x198-VD	60	M24	241	244	198	43	24	24	24	18000	751	△

PS. 備註

・使用溫度：-30°C~100°C

訂貨： 交期： 天

188101

SP. 特長

- ・由RAL 5005「藍」PA製成，符合FDA標準(FDA CFR.21和EU 10/2011)，適合用於食品行業，可輕鬆用人眼辨別食品污染，目檢容易
- ・有防滑墊的底座具有優良的固定性能

WA. 注意

- ・如果超過上表最大靜態荷重，可能會導致底座破裂
- ・為防止運送途中碰傷，腳座(底座與螺柱)採用個別包裝，請客戶自行組立
- ・螺帽需個別購買