




品號	D 0 -0.1	W 0 -0.2	C ±0.4	L ±0.5	使用 六角扳手	荷重 (N)	庫存
K-DR-22-B0.5-JH	22	7	0.5	M6×8	4	196	
K-DR-24-B0.5-JH	24						
K-DR-26-B0.5-JH	26						
K-DR-28-B0.5-JH	28						
K-DR-30-B0.5-JH	30						
K-DR-35-B0.5-JH	35						




品號	D 0 -0.1	W 0 -0.2	C ±0.4	L ±0.5	使用 六角扳手	荷重 (N)	庫存
K-DO-22-B0.5-JH	22	7	0.5	M6×8	4	196	
K-DO-24-B0.5-JH	24						
K-DO-26-B0.5-JH	26						
K-DO-28-B0.5-JH	28						
K-DO-30-B0.5-JH	30						
K-DO-35-B0.5-JH	35						




品號	D ±0.2	D1 ±0.1	W 0 -0.2	C ±0.4	L ±0.5	使用 六角扳手	荷重 (N)	庫存
K-DU-22-B0.5-JH	22	19.2	7	0.5	M6×8	4	156	
K-DU-24-B0.5-JH	24	21.2						
K-DU-26-B0.5-JH	26	23.2						
K-DU-28-B0.5-JH	28	24						
K-DU-30-B0.5-JH	30	25.7						
K-DU-35-B0.5-JH	35	31						



品號	D ±0.2	D1 ±0.2	W 0 -0.2	C ±0.4	L ±0.5	使用 六角扳手	荷重 (N)	庫存
K-DV-22-B0.5-JH	22	19	7	0.5	M6×8	4	156	
K-DV-24-B0.5-JH	24	21						
K-DV-26-B0.5-JH	26	23						
K-DV-28-B0.5-JH	28	24						
K-DV-30-B0.5-JH	30	27						



品號	D ±0.2	D1 ±0.2	W 0 -0.2	C ±0.4	L ±0.5	使用 六角扳手	荷重 (N)	庫存
K-DH-19-B0.5-2-JH	22	19	7	0.5	M6×8	4	49	
K-DH-21-B0.5-2-JH	24	21					156	



品號	D	W	C ±0.4	L ±0.5	使用 六角扳手	荷重 (N)	庫存
K-ER-22-B0.5-JH	22±0.2	7 ⁰ _{-0.2}	0.5	M6×8	4	49	
K-ER-24-B0.5-JH	24 ⁰ _{-0.1}						
K-ER-26-B0.5-JH	26 ⁰ _{-0.1}						
K-ER-28-B0.5-JH	28 ⁰ _{-0.1}						
K-ER-30-B0.5-JH	30 ⁰ _{-0.1}						
K-ER-35-B0.5-JH	35 ⁰ _{-0.1}						

Sp 特長

- 高緊固力可防止鬆動，提高可靠性
- 適用狹窄的空間和工作效率的提高

訂貨： 交期：

K-DR-22-B0.5-JH

Ps 備註

- 溫度範圍：0°C~40°C
- 滾輪請勿施予軸向荷重
- 容許荷重是本公司300RPM/100萬回的測試值
- 1N=0.101972kgf

Wa 注意

- 非庫存品必須以101pcs為單位購買之