





材質	顏色
PU	藍、黑、紅



SORB-A



SORB-B



SORB-C

片狀 TYPE	1	2	厚度 公差	3	W×L	庫存
	蕭氏硬度	t mm		顏色		
SORB-A	S (30°)	0.3	±0.15	BL (藍)  B (黑)  R (紅)	100×300	△
		0.5				△
		0.8				△
		1				△
		1.5				△
		2				△
	M (50°)	2.5	±0.3		300×300	△
		3				△
		4				△
	H (70°)	5	±0.8			△
		6				△
		7				△
		10		△		
		15		△		
		20		△		
	25		△			
	30		△			

訂貨： TYPE - 1 硬度 - 2 t - 3 顏色 交期：請洽詢

SORB-A - S - 0.3 - BL



圓柱 TYPE	蕭氏 硬度	1	2	3	顏色	壓縮量範圍 mm	荷重範圍 kgf			庫存
		D	H	S(30°)			M(50°)	H(70°)		
SORB-B	S (30°)	10	7	BL (藍)	0.30-1.10	0.06-1.19	0.13-0.45	0.40-1.40	△	
					0.50-1.50	0.13-0.45	0.32-1.09	1.02-3.49	△	
		15	10		0.30-1.10	0.15-0.51	0.34-1.19	1.08-3.81	△	
					0.70-2.30	0.24-0.79	0.55-1.85	1.72-5.86	△	
		20	15		10	0.50-1.50	0.26-0.89	0.67-2.41	1.83-6.37	△
	1.0-3.0					2.54-9.43	5.58-20.20	13.93-49.93	△	
	M (50°)	65	30		B (黑)	1.5-4.5	3.18-11.43	6.66-24.31	17.07-63.83	△
						2.0-6.0	4.42-15.37	9.47-32.98	25.05-85.06	△
		75	40			1.5-4.5	4.80-17.34	10.60-38.38	25.86-92.28	△
						2.0-6.0	7.61-27.05	16.05-59.60	39.11-140.43	△
		95	40	R (紅)		1.5-4.5	8.26-32.16	19.16-70.95	37.97-146.30	△
	2.5-7.5					13.21-49.31	27.91-99.20	67.30-256.15	△	
	125	35	1.8-5.3			14.74-65.07	35.17-142.82	86.29-336.90	△	
			2.5-7.5			20.77-79.65	40.02-156.54	98.63-383.93	△	
	150	50	1.8-5.3			25.92-111.42	50.75-222.59	129.28-540.00	△	
			35							

訂貨： TYPE - 硬度 - D - H - 顏色 交期：請洽詢  
SORB-B - S - 10 - 7 - BL

圓柱中空 TYPE	蕭氏 硬度	1	2	3	4	顏色	壓縮量範圍 mm	荷重範圍 kgf			庫存
		D	d	H	S(30°)			M(50°)	H(70°)		
SORB-C	S (30°)	10	5	7	BL (藍)	0.30-1.10	0.04-0.14	0.09-0.31	0.29-1.00	△	
						0.50-1.50	0.11-0.38	0.25-0.83	0.65-2.19	△	
		15	7	10		0.30-1.10	0.12-0.42	0.25-0.88	0.63-2.32	△	
						0.70-2.30	0.19-0.63	0.39-1.30	1.00-3.33	△	
		20	10	15		0.50-1.50	0.20-0.69	0.43-1.51	1.04-3.81	△	
	1.0-3.0					1.68-5.96	3.71-12.99	10.22-35.82	△		
	M (50°)	65	35	B (黑)		1.5-4.5	2.36-8.07	4.97-16.76	13.19-45.79	△	
						2.0-6.0	2.83-10.47	5.80-20.33	14.38-51.92	△	
		75	40			2.0-6.0	2.90-9.94	5.93-20.32	16.83-56.54	△	
						1.5-4.5	3.27-11.84	7.15-24.15	19.18-65.83	△	
		95	50		R (紅)	2.0-6.0	5.13-18.30	11.46-39.86	24.63-93.51	△	
	1.5-4.5					6.16-21.83	13.03-45.49	32.19-114.00	△		
	125	65	2.5-7.5			10.19-35.36	20.86-72.16	50.22-180.95	△		
			1.8-5.3			10.15-38.71	18.67-81.76	54.88-202.35	△		
	150	75	2.5-7.5			17.14-61.74	32.66-114.32	83.00-287.63	△		
			1.8-5.3			14.83-65.63	37.94-152.68	84.80-323.56	△		

PS. 備註

· 在厚度為1.0~1.1mm時，進行耐燃測試，達UL94-HB標準，可自熄

訂貨： TYPE - 硬度 - D - d - H - 顏色 交期：請洽詢  
SORB-C - S - 10 - 5 - 7 - BL