

PE導位槽軌系統 ^{鏈條導位}



(RoHS)







軌道	C槽軌			
材質	顏色	材質	處理	
PE (UHMWPE)	綠	鋼	鍍鋅	

品	號	鏈條 NO.	Α	В	С	D	E	F	G	Н	J	K	L	質量 (g/m)	定寸 (m)	庫存	切斷費 (NT/刀)
AG	C35S	35	4.4	2.2	17	22	20	16	18	10	21	10	1.5	710		Δ	
AG	C40S	40	7.6	2.3	24	30	28	20	23	12	27	14 2	2	1270	2	Δ	
AG	C50S	50	9.1	2.7	28	36		22	27		31			1400		Δ	
AG	C60S	60	12.2	3.4	35	44	38	30	36	18	41	22	2.5	2400		Δ	
AG	C80S	80	15.3	4.6	44	54		33	43		48			2670		Δ	

安裝推薦

螺絲尺寸

M4

M5

品號

AGC35S AGC40S AGC50S


AGC60S

AGC80S

Wa. 注意

- · 適用鏈條是單列傳導用輥子鏈條和襯套鏈條 (JIS B1801)
- · 2m以內的切斷販賣價格是產品單價+切斷費 (切斷後端材餘料長度大於500mm以上時,端材餘料 也會一起寄送;但餘料長度小於500mm以下時,除非 貴司指定,否則不寄送)
- ·長度在溫度變化1°C時,1000mm的伸縮量約0.2mm (庫存品的長度變化量亦有可能比較大)
- · 考慮到伸縮量的變化,請用長孔型設計

■安裝例



品 號	安裝推薦 螺絲尺寸					
AGC35S	M4					
AGC40S	M5					
AGC50S	M6					
AGC60S	IND					
AGC80S	M8					

- ·C軌道可溶接
- ·安裝螺絲的前端和頭部不要凸出表面
- · 追加工詳細請參考本單元



AGC35S