



① 拉拔螺紋尺寸大於
安裝螺栓一個規格

安裝螺栓	M(拉拔螺紋)
M3	M4
M4	M5
M6	M8
M8	M10

材質	硬度
相當於SKD11	60~63HRC

K	安裝螺栓			J	Catalog No	V	H	L	P		
	d	h	規格								
4	6	7.5	M3	3	TTLT	13	8	16	0.8		
				4		16					
				5		18					
				6.5		20					
5	8	8.5	M4	4		18	10			20	
				5		20					
				6.5		22					
				8		25					
6.5	11	10.5	M6	5		22	13			22	
				6.5		25					
				8		28					
				10		32					
				6.5		25		16			25
				8		28					
10	32										
12.5	38										
8	14	12.5	M8	8		32	20	30			
				10		35					
				12.5		40					
				15		45					
				10	35	25		35			
				12.5	40						
				15	45						
				17.5	50						

追加加工 訂貨: Catalog No [] V [] H [] - L(LC) [] - (CC·LKC...etc) TTLT 25 13 - LC17.0 - LKC

訂貨: Catalog No [] V [] H [] - L [] 交期: 15 天 TTLT 25 13 - 25

Alteration	Code	Spec.
全長追加加工	LC	變更全長 16 < LC < L 指定0.1mm單位 (LKC、LKZ併用時, 指定0.01mm單位)
	LKC	變更全長公差 L _{+0.2} ^{+0.4} → L ₀ ^{+0.05}
	LKZ	變更全長公差 L _{+0.2} ^{+0.4} → L ₀ ^{+0.01}

Alteration	Code	Spec.
=	VKC1	變更V·H公差 V·H ₀ ^{+0.01} → V·H ₀ ^{+0.005}
	VKC2	變更V·H公差 V·H ₀ ^{+0.01} → V·H ₀ ^{-0.005}
其它	CC	外周(V·H)角部4處 進行C0.5倒角處理
	NDC	無導入部
	NHC	無孔(P)