




| 材質 | 硬度 | 備註 |
|--------|----------|---------|
| ASP-60 | HRC67~69 | 高鈷粉末高速鋼 |



| Type | T +0.4 +0.2 | W | L | 單價 |
|--------|-------------------|----|-----|----|
| ASP-60 | 1.5 | 50 | 150 | • |
| | 2 | | | • |
| | 3 | | | • |
| | 4 | | | • |
| | 5 | | | • |
| | 6 | | | • |
| | 7 | | | • |
| | 8 | | | • |
| | 9 | | | • |

| Type | T +0.4 +0.2 | W | L | 單價 |
|--------|-------------------|-----|-----|----|
| ASP-60 | 10 | 150 | 200 | • |
| | 12 | | | • |
| | 15 | | | • |
| | 18 | | | • |
| | 20 | | | • |
| | 22 | | | • |
| | 25 | | | • |
| | 30 | | | • |
| | 35 | | | • |
| | 40 | | | • |
| | 50 | | | • |
| | 60 | | | • |

Wa. 注意

- ・兩面研磨加工,平坦度佳
- ・可研磨加工成爲各種刀具、治具
或作爲線割板用

Sp. 特長

- ・高耐磨

訂貨: TYPE - T - W - L 交期: 3 天

ASP-60 - 1.5 - 50 - 150