


RoHS



K	D		L	
±10%	≤8.5 ±0.3	≥10.6 ±0.4	≤50 ±1	≥60 ±2

Type	材質	顏色
NAL · NAM	SWP	本色

銷徑	品號		D ₁ 外徑 mm	D 內徑 mm	d 線徑 mm	L 自由長 mm	F max	密著長 mm	定數 N/mm	F=L×40%		單價	銷徑	品號		D ₁ 外徑 mm	D 內徑 mm	d 線徑 mm	L 自由長 mm	F max	密著長 mm	定數 N/mm	F=L×32%		單價
	Type	D-L								荷重 N(max)	荷重 N(max)			Type	D-L								荷重 N(max)	荷重 N(max)	
5	NAL	5.5-30	7.0	5.5	0.75	30	12	10.9	1.1	13.2	•		5	NAM	5.5-30	7.3	5.5	0.9	30	9.6	13.1	2.1	•		
		35				14	12.0	1.0	14.0	35					11.2				14.9	1.8	20.2				
		40				16	13.5	0.9	14.4	40					12.8				16.2	1.6	20.5				
		45				18	15.0	0.8	14.4	45					14.4				18.0	1.4	20.2				
		50				20	16.5	0.7	14.0	50					16.0				19.8	1.3	20.8				
6	NAL	6.5-30	8.1	6.5	0.8	30	12	9.6	1.1	13.2	•		6	NAM	6.5-30	8.5	6.5	1.0	30	9.6	14.0	2.1	•		
		35				14	10.8	1.0	14.0	35					11.2				15.5	1.8	20.2				
		40				16	12.0	0.9	14.4	40					12.8				17.5	1.6	20.5				
		45				18	13.2	0.8	14.4	45					14.4				19.5	1.4	20.2				
		50				20	14.4	0.7	14.0	50					16.0				21.0	1.3	20.8				
8	NAL	8.5-30	10.5	8.5	1.0	30	12	9.8	1.7	20.4	•		8	NAM	8.5-30	10.7	8.5	1.1	30	9.6	9.4	2.9	27.8	•	
		35				14	10.8	1.5	21.0	35					11.2				10.5	2.5	28.0				
		40				16	12.0	1.3	20.8	40					12.8				11.6	2.1	26.9				
		45				18	13.0	1.1	19.8	45					14.4				12.7	1.9	27.4				
		50				20	14.0	1.0	20.0	50					16.0				13.8	1.7	27.2				
		60				24	16.5	0.9	21.6	60					19.2				16.0	1.4	26.9				
10	NAL	10.6-30	12.8	10.6	1.1	30	12	9.1	1.7	20.4	•		10	NAM	10.6-30	13.2	10.6	1.3	30	9.6	11.4	2.9	27.8	•	
		35				14	9.9	1.5	21.0	35					11.2				12.7	2.5	28.0				
		40				16	11.0	1.3	20.8	40					12.8				14.0	2.1	26.9				
		45				18	12.1	1.1	19.8	45					14.4				15.3	1.9	27.4				
		50				20	12.7	1.0	20.0	50					16.0				16.6	1.7	27.2				
		60				24	14.9	0.9	21.6	60					19.2				19.2	1.4	26.9				
13	NAL	13.6-35	16.4	13.6	1.4	35	14	12.3	2.0	28.0	•		13	NAM	13.6-35	16.8	13.6	1.6	35	11.2	14.4	3.1	34.7	•	
		40				16	13.3	1.7	27.2	40					12.8				15.6	2.7	34.6				
		45				18	14.7	1.5	27.0	45					14.4				17.2	2.4	33.6				
		50				20	15.8	1.4	28.0	50					16.0				18.4	2.1	33.6				
		60				24	18.2	1.1	26.4	60					19.2				20.8	1.8	34.6				
		60				24	18.2	1.1	26.4	60					19.2				20.8	1.8	34.6				
16	NAL	16.6-35	19.8	16.6	1.6	35	14	13.6	2.0	28.0	•		16	NAM	16.6-35	20.2	16.6	1.8	35	11.2	15.3	3.1	34.7	•	
		40				16	14.8	1.7	27.2	40					12.8				16.7	2.7	34.6				
		45				18	16.0	1.5	27.0	45					14.4				18.5	2.4	33.6				
		50				20	17.2	1.4	28.0	50					16.0				19.4	2.1	33.6				
		60				24	20.0	1.1	26.4	60					19.2				22.5	1.8	34.6				
		60				24	20.0	1.1	26.4	60					19.2				22.5	1.8	34.6				

PS. 備註

- 荷重(N)=定數(N/mm)×壓縮量(mm)
- 密著長是參考值,製作時會有少許差異
- 耐熱溫度80°C
- 1N=0.101972 kgf
- NAL/NAM全部兩端研磨

訂貨: 交期: 天

NAL5.5-30