




TYPE	TU44	FTU66	FTU88
截面	 4.5×4.5 ±0.15	 6.0×6.0 ±0.15	 8.0×8.0 ±0.15
不加熱長度	Luh = 30 ±5.0	Luh = 30 ±5.0	Luh = 30 ±5.0
最大表面荷載	10 W/cm <sup>2</sup>	10 W/cm <sup>2</sup>	10 W/cm <sup>2</sup>

TYPE	L	瓦特數 (W)	端口型式	電壓 (V)	TYPE	L	瓦特數 (W)	端口型式	電壓 (V)	TYPE	L	瓦特數 (W)	端口型式	電壓 (V)
FTU44	300	250	A B C	230	FTU66	*300	450	A B C	230	FTU66	*800	1350	A B C	230
	350	300				320	490				820	1390		
	400	350				340	530				840	1430		
	450	400				360	570				860	1470		
	500	450				380	610				880	1510		
	550	500				*400	650				*900	1550		
	600	550				420	680				920	1590		
	650	600				440	710				940	1630		
	700	650				460	740				960	1670		
	750	700				480	770				980	1710		
	800	750				*500	800				*1000	1750		
	850	800				520	840				1050	1850		
	900	850				540	880				1100	1950		
	950	900				560	920				1150	2100		
	1000	950				580	960				1200	2200		
	1050	1000				*600	1000				1250	2200		
	1100	1050				620	1040				1300	2300		
1150	1100	640	1080	1350	2400									
1200	1150	660	1120	1400	2500									
1250	1200	680	1160	1450	2600									
1300	1250	*700	1200	1500	2700									
1350	1300	720	1230											
1400	1350	740	1260											
1450	1400	760	1290											
1500	1450	780	1320											

TYPE	L	瓦特數 (W)	端口型式	電壓 (V)	TYPE	L	瓦特數 (W)	端口型式	電壓 (V)	TYPE	L	瓦特數 (W)	端口型式	電壓 (V)
FTU88	*300	750	A B C	230	FTU88	*700	2000	A B C	230	FTU88	1250	3300	A B C	230
	320	810				720	2060				1300	3300		
	340	870				740	2120				1350	3300		
	360	930				760	2180				1400	3300		
	380	990				780	2240				1450	3400		
	*400	1050				*800	2300				1500	3500		
	420	1120				820	2360							
	440	1190				840	2420							
	460	1260				860	2480							
	480	1330				880	2540							
	*500	1400				*900	2600							
	520	1460				920	2660							
	540	1520				940	2720							
	560	1580				960	2780							
	580	1640				980	2840							
	*600	1700				*1000	2900							
	620	1760				1050	3050							
	640	1820				*1100	3200							
660	1880	1150	3250											
680	1940	*1200	3300											

**Ps. 備註**


- 單位：mm
- 內附PTFE絕緣導線
- 本產品通過CE認證
- 標準品為直棒，如需彎曲請先告知

**Wa. 注意**

- 直徑為8×8才可選擇端口型式：A-M4

**Be. 彎曲資訊**

- 如需彎曲，請附圖面
- 為了保障加熱器壽命熱傳導品質請依下列尺寸加工



訂貨： TYPE - L - 瓦特數 - 端口型式

FTU44 - 300 - 250 - A-M2.5 (端口型式A)

FTU44 - 300 - 250 - B (端口型式B或C)

交期： 4 天 \*記號

16 天 其它

參閱本系列首頁或掃描QR Code	
端口型式	
A	螺紋端口
B	陶瓷接線柱
C	插接型端口



TYPE	W 寬度	H 高度	ID 彎曲內徑
FTU44	4.6 <sup>+0.1</sup> / <sub>-0</sub>	4.6 <sup>+0</sup> / <sub>-0.2</sub>	> 16.0
FTU66	6.1 <sup>+0.1</sup> / <sub>-0</sub>	6.1 <sup>+0</sup> / <sub>-0.2</sub>	> 18.0
FTU88	8.1 <sup>+0.1</sup> / <sub>-0</sub>	8.1 <sup>+0</sup> / <sub>-0.2</sub>	> 20.0

