



TYPE	截面	最小內徑	瓦特數公差	電阻	抗電強度	絕緣(冷500V)	微漏電流	套管允許最高工作溫度
RM30	● 3.0 ±0.1	8 mm	± 10 %	± 10 %	1000 V	> 10 MΩ	< 0.5 mA	750 °C
RM40	● 4.0 ±0.1	12 mm			1250 V			

TYPE	L	瓦特數 (W)	導線披覆型式	L1	D1	D2	電壓 (V)
RM30 (無感溫線)	200	150	A B	20	7.0	5.5	230
	250	175					
	300	200					
	350	225					
	400	250					
	450	290					
	500	330					
	600	400					
	700	470					
	800	550					
RM30TC (有感溫線)	900	620	A B	20	7.0	5.5	230
	1000	700					
	250	175					
	300	200					
	350	225					
	400	250					
	450	290					
	500	330					
	600	400					
	700	470					
RM40 (無感溫線)	800	550	A B	25	8.5	6.5	230
	900	620					
	1000	700					
	1200	850					
	1400	950					
	1600	1100					
	1800	1200					
	250	175					
	300	200					
	350	225					
400	250						
450	290						
500	330						
600	400						
700	470						
RM40TC (有感溫線)	800	550	A B	25	8.5	6.5	230
	900	620					
	1000	700					
	1200	850					
	1400	950					
	1600	1100					
	1800	1200					
	250	175					
	300	200					
	350	225					
400	250						
450	290						
500	330						
600	400						
700	470						

Ps. 備註

- 單位：mm
- 內附PTFE絕緣導線
- 本產品通過CE認證
- 追加工訂貨參閱本系列首頁或掃描QR Code

訂貨：TYPE - L - 瓦特數 - 導線披覆型式 交期：請洽詢

RM30 - 200 - 150 - A

參閱本系列首頁或掃描QR Code	
導線披覆型式	
A	玻璃纖維
B	金屬編織網

