



TYPE	截面	最小內徑	瓦特數公差	電阻	抗電強度	絕緣(冷500V)	微漏電流	套管允許最高工作溫度
KH2314	2.3×1.4 ±0.1	6 mm	± 10 %	± 10 %	800 V	> 10 MΩ	< 0.5 mA	750 °C
KH3030	3.0×3.0 ±0.1							
KH3218	1.8×3.2 ±0.1	8 mm			1000 V			

TYPE	L	瓦特數 (W)	導線披覆型式	L1	D1	D2	電壓 (V)	
KH2314 (無感溫線)	120	80	A B	15	6.0	4.5	230	
	150	100						
	200	125						
	250	150						
	300	175						
	KH2314TC (有感溫線)	350						200
		400						225
450		250						
500		275						
KH3030 (無感溫線)	390	215	A B	20	7.0	5.5	230	
	540	325						
	740	470						
	940	610						
	1140	630						
	KH3030TC (有感溫線)	1400						950
		1690						1100
		1890						1250
2090		1400						
KH3218 (無感溫線)	200	150	A B	20	7.0	5.5	230	
	250	175						
	300	200						
	350	225						
	400	250						
	450	290						
	500	330						
	600	400						
	700	470						
	800	550						
	900	620						
1000	700							

備註

- 單位：mm
- 內附PTFE絕緣導線
- 本產品通過CE認證
- 追加工訂貨參閱本系列首頁或掃描QR Code

訂貨： TYPE - L - 瓦特數 - 導線披覆型式 交期：請洽詢

KH2314 - 120 - 80 - A

參閱本系列首頁或掃描QR Code	
導線披覆型式	
A	玻璃纖維
B	金屬編織網

