



TYPE	截面	最小內徑	瓦特數公差	電阻	抗電強度	絕緣(冷500V)	微漏電流	套管允許最高工作溫度
KH3232	3.2×3.2 ±0.1	12 mm	± 10 %	± 10 %	1250 V	> 10 MΩ	< 0.5 mA	750 °C
KH4025	4.0×2.5 ±0.1							
KH4222	4.2×2.2 ±0.1							

TYPE	L	瓦特數 (W)	導線披覆型式	L1	D1	D2	電壓 (V)						
KH3232 (無感溫線)	250	175	A B	25	8.5	6.5	230						
	300	200											
	350	225											
	400	250											
	450	290											
	500	330											
	600	400											
	700	470											
	KH3232TC (有感溫線)	800						550	A B	25	8.5	6.5	230
		900						620					
1000		700											
1200		850											
1400		950											
1600		1100											
1800		1200											
KH4025 (無感溫線)		250	200	A B	25	8.5	6.5	230					
		300	225										
		350	250										
	400	290											
	450	330											
	500	400											
	600	470											
	KH4025TC (有感溫線)	700	550						A B	25	8.5	6.5	230
		800	620										
		900	700										
1000		800											
1200		950											
1400		1100											
1600		1200											
KH4222 (無感溫線)		340	195	A B	25	8.5	6.5	230					
		370	215										
		425	240										
	475	295											
	550	350											
	610	400											
	690	460											
	KH4222TC (有感溫線)	580	610						A B	25	8.5	6.5	230
		990	690										
		1200	850										
1400		950											
1690		1100											
1890		1250											
2090		1400											

備註

- 單位：mm
- 內附PTFE絕緣導線
- 本產品通過CE認證
- 追加工訂貨參閱本系列首頁或掃描QR Code

訂貨： TYPE - L - 瓦特數 - 導線披覆型式 交期：請洽詢

KH3232 - 250 - 175 - A

參閱本系列首頁或掃描QR Code	
導線披覆型式	
A	玻璃纖維
B	金屬編織網

