



TYPE	截面	最小內徑	瓦特數公差	電阻	抗電強度	絕緣(冷500V)	微漏電流	套管允許最高工作溫度
KH4322	4.3×2.2 ±0.1	12 mm	± 10 %	± 10 %	1250 V	> 10 MΩ	< 0.5 mA	750 °C
KH5030	5.0×3.0 ±0.1	18 mm						
KH6040	4.0×6.0 ±0.1	24 mm			1500 V			

TYPE	L	瓦特數 (W)	導線披覆型式	L1	D1	D2	電壓 (V)
KH4322 (無感溫線) KH4322TC (有感溫線)	250	200	A B	25	8.5	6.5	230
	300	225					
	350	250					
	400	290					
	450	330					
	500	400					
	600	470					
	700	550					
	800	620					
	900	700					
	1000	800					
	1200	950					
1400	1100						
1600	1200						
KH5030 (無感溫線) KH5030TC (有感溫線)	800	700	A B	28	9.5	7.5	230
	900	800					
	1000	900					
	1200	1050					
	1400	1200					
	1600	1300					
	1800	1400					
	2000	1500					
2200	1600						
KH6040 (無感溫線) KH6040TC (有感溫線)	800	800	A B	30	7.5	9.5	230
	1000	1000					
	1250	1200					
	1500	1400					
	1750	1600					
	2000	1800					
	2250	2000					
	2500	2200					

Ps) 備註

- 單位：mm
- 內附PTFE絕緣導線
- 本產品通過CE認證
- 追加工訂貨參閱本系列首頁或掃描QR Code

訂貨： TYPE - L - 瓦特數 - 導線披覆型式 交期：請洽詢

KH4322 - 250 - 200 - A

參閱本系列首頁或掃描QR Code	
導線披覆型式	
A	玻璃纖維
B	金屬編織網

