



TYPE	材質	硬度(HRC)	表面處理
PSN	相當於SKD11	60~63HRC	-
B-PSN	相當於SKD11	60~63HRC 表面3000HV	DICOAT®
PIN	相當於SKH51	61~64HRC	-

· 頂料孔詳情請參閱沖頭單元基本型沖頭

Catalog No.		L	TYPE	V	P	B	S	E	M × P	d: 下模內徑, h: 翻邊高度, 被加工材料: SPCC(實驗值)						
TYPE	M									d \ h	t	0.6	0.8	1.0	1.2	1.6
PSN B-PSN	2.6	41 51 61 71	A	2.22	1.5	6	2	2.7	M2.6 × 0.45	d	3.12	3.34	3.72			
			h	1.3						1.47	1.77					
			d	3.15						3.37	3.75					
			h	1.3						1.5	1.8					
PSN B-PSN PIN	3		A	2.59	1.9	8	3	3.6	M3 × 0.5	d	3.22	3.44	3.82			
			h	1.35						1.6	1.82					
			d	3.25						3.47	3.85					
			h	1.35						1.6	1.82					
			d	3.49						3.79	3.99	4.39				
			h	1.3						1.55	1.75	2.05				
	4		A	2.63	2.4	8	3	3.7	M4 × 0.7	d	3.53	3.83	4.03	4.43		
			h	1.35						1.6	1.75	2.07				
		d	3.62	3.92						4.12	4.52					
		h	1.37	1.6						1.77	2.1					
		d	3.66	3.96						4.16	4.56					
		h	1.4	1.65						1.8	2.15					
5	A	3.39	2.8	8	4	5.4	M5 × 0.8	d	4.29	4.59	4.79	5.07	5.79			
	h	1.5						1.77	2.0	2.17	2.6					
	d	4.34						4.64	4.84	5.12	5.84					
	h	1.5						1.77	2.0	2.2	2.65					
	d	4.54						4.84	5.04	5.32	6.04					
	h	1.6						1.85	2.07	2.27	2.7					
	d	4.59						4.89	5.09	5.37	6.09					
	h	1.63						1.9	2.1	2.3	2.73					
5	A	4.33	2.8	8	4	5.6	M5 × 0.8	d			5.83	6.01	6.57	7.33		
	h								2.27	2.47	2.85	3.5				
	d								5.88	6.06	6.62	7.38				
	h								2.3	2.52	2.9	3.52				
	d								6.12	6.30	6.86	7.62				
	h								2.42	2.65	3.0	3.62				
	d								6.17	6.35	6.91	7.67				
	h								2.45	2.7	3.05	3.65				

**Wa** 注意

- 必須變更全長L、S等尺寸時,請利用拉伸沖頭的8C形狀(請參閱本單元拉伸沖頭(前端形狀))
- 尺寸指定型規格請參閱本單元翻邊沖頭(前端R型)

訂貨: Catalog No. - L - TYPE 交期: 13 天

PSN 4 - 61 - B