



材質	硬度	螺紋精度	平面偏擺	平行度	同心度
SCM440	HRC48~52	ISO 4H 精密研磨	0.002mm	0.002mm	0.005mm

品號	螺牙	D	h	d	φ U × V	C	F	M × n	扭緊力矩 (max.Nm)	鬆脫力矩	單價
SBL-A-0002	M 20×1	38	16	33	4.3×3	13	5	M 5×6	4.5	28.9	•
SBL-A-0004	M 20×1.5										
SBL-A-0006	M 25×1.5										
SBL-A-0008	M 30×1.5	45	18	40		16		M 6×6	8	30.4	•
SBL-A-0010	M 35×1.5					19				32.4	•
SBL-A-0012	M 40×1.5	52	20	47		22		M 8×6	18	39.2	•
SBL-A-0014	M 45×1.5					25				46.1	•
SBL-A-0016	M 50×1.5					28				70.6	•
SBL-A-0018	M 55×2					30				88.2	•
SBL-A-0020	M 60×2	75	22	68		33		M 8×6	18	98	•
SBL-A-0022	M 65×2				35	127.5	•				
SBL-A-0024	M 70×2				38	147.1	•				
SBL-A-0026	M 75×2	85	24	84	41	M 10×6	35	152	•		
SBL-A-0028	M 80×2				43			156.9	•		
SBL-A-0030	M 85×2				46			176.5	•		
SBL-A-0032	M 90×2				49			186.3	•		
SBL-A-0034	M 95×2	105	26	102	53	M 10×6	35	201	•		
SBL-A-0036	M100×2				55			220.6	•		
SBL-A-0038	M105×2				58			236.3	•		
SBL-A-0040	M110×2	120	28	108	61	M 10×6	35	252	•		
SBL-A-0042	M115×2				64			268.1	•		
SBL-A-0044	M120×2				66			279.4	•		
SBL-A-0046	M125×2				69			289.2	•		
SBL-A-0048	M130×2	130	30	113	71	M 10×6	35	313.7	•		
SBL-A-0050	M135×2				74			352.9	•		
SBL-A-0052	M140×2				77			392.2	•		
SBL-A-0054	M145×2	140	32	118	80	M 10×6	35	436.3	•		
SBL-A-0056	M150×2				84			480.4	•		
SBL-A-0056	M150×2	150	142	125	6.4×3	7	7	86			

Wa) 注意

- 鎖定方式為螺紋半角30°六點式鎖定,比三點式鎖定更為優異,能使六個固定鋼平均完全契合於公螺紋上,使其防鬆效果完美
- 螺帽本身內螺紋、端面、背面、外圓都經過精密研磨加工,降低其在高速旋轉下所可能產生的平衡問題和風切的噪音問題
- 1 Nm = 10.2 kgf.cm = 0.73 lb.ft

訂貨: 交期:

SBL-A-0002