


本體	彈簧	銷子
材質	材質	材質 處理
SUS303	SUS	SUS303 氮化

無耐落	庫存	有耐落	庫存	備註	A	螺紋規格	B	C	D	WS	荷重(lbs)		質量 (oz)
品號		品號									F1 ≈	F2 ≈	
2B030.0133	•	2B030.0333	•	中荷重	6-32	2A-UNC	0.046	17/32	0.063	1/16	0.5	1.5	0.018
2B030.0136	•	2B030.0336	•		8-32		0.070	5/ 8	0.094	5/64	0.8	2.3	0.039
2B030.0140	•	2B030.0340	•		10-32	2A-UNF	0.093	3/ 4	0.125	3/32	1.4	2.7	0.063
2B030.0142	•	2B030.0342	•		1/ 4-20	2A-UNC	0.119	1	0.188	1/ 8	1.0	4.0	0.131
2B030.0144	•	2B030.0344	•		1/ 4-28	2A-UNF							0.141
2B030.0146	•	2B030.0346	•		5/16-18	2A-UNC	0.135	1 1/ 8	0.250	5/32	1.5	4.5	0.208
2B030.0148	•	2B030.0348	•		3/ 8-16		0.186			3/16	2.7	7.2	0.328
2B030.0150	•	2B030.0350	•		1/ 2-13		0.248	1 1/ 4	0.313	1/ 4	2.7	9.3	0.653
2B030.0152	•	2B030.0352	•		5/ 8-11		0.310	1 1/ 2		5/16	3.5	10.6	1.242
2B030.0153	•	2B030.0353	•		3/ 4-10		0.374	1 3/ 4	3/ 8	5.5	14.5	2.180	
2B030.0154	•	2B030.0354	•		1- 8		0.499	2 13/32		0.50	4.0	31.0	5.474
2B030.0163	•	2B030.0363	•	重荷重	6-32	2A-UNC	0.046	17/32	0.063	1/16	1.5	3.4	0.025
2B030.0166	•	2B030.0366	•		8-32		0.070	5/ 8	0.094	5/64	2.6	6.6	0.042
2B030.0170	•	2B030.0370	•		10-32	2A-UNF	0.093	3/ 4	0.125	3/32	3.2	9.0	0.063
2B030.0172	•	2B030.0372	•		1/ 4-20	2A-UNC	0.119	1	0.188	1/ 8	3.1	10.1	0.131
2B030.0174	•	2B030.0374	•		1/ 4-28	2A-UNF							0.145
2B030.0176	•	2B030.0376	•		5/16-18	2A-UNC	0.135	1 1/ 8	0.250	5/32	3.0	15.0	0.212
2B030.0178	•	2B030.0378	•		3/ 8-16		0.186			3/16	5.5	12.7	0.339
2B030.0180	•	2B030.0380	•		1/ 2-13		0.248	1 1/ 4	0.313	1/ 4	6.6	16.0	0.653
2B030.0182	•	2B030.0382	•		5/ 8-11		0.310	1 1/ 2		5/16	10.5	22.2	1.252
2B030.0183	•	2B030.0383	•		3/ 4-10		0.374	1 3/ 4	3/ 8	6.7	33.0	2.198	
2B030.0184	•	2B030.0384	•		1- 8		0.499	2 13/32		0.50	16.0	60.0	5.524

Wa. 注意


- ・無耐落使用溫度-30℃~+250℃
有耐落使用溫度-30℃~+ 90℃
- ・1lbs=4.45N
- ・中荷重定位珠牙部無雷射線



- ・重荷重定位珠牙部有兩條雷射線



Ex. 使用例


 訂貨： 品號 交期： 1 天

2B030.0133