



RoHS SUS



Type	本體		銷子	
	材質	處理	材質	處理
分割定位柱	鋼	染黑	鋼	硬化
專用扳手	SUS303	-	SUS303	鍍鎳
	鋼	染黑	-	-

鋼 品號	庫存	不銹鋼 品號	庫存	備註	A -0.02 -0.04	B	D ≈	E	G min.	K	N	荷重(N)		質量 (g)
												F1 ≈	F2 ≈	
22120.0065	•	22120.0465	•	分割定位柱	5	M10×1.0	33	22	5	6	M5	6.0	14	12.0
22120.0066	•	22120.0466	•		6	M12×1.5	42	26	6	10	M6	5.5	13	12.0
22120.0068	•	22120.0468	•		8	M16×1.5	54	34	8	12	M8	11.5	28	46.0
22120.0070	•	22120.0470	•		10	M20×1.5	65	43	10			23.0	54	87.0
22120.0115	•	22120.0515	•	螺帽	-	M10×1.0	-	-	-	-	-	-	-	5.2
22120.0116	•	22120.0516	•			M12×1.5								7.4
22120.0118	•	22120.0518	•			M16×1.5								18.0
22120.0120	•	22120.0520	•			M20×1.5								32.0
22120.0955	•	-	-	專用扳手	-	M10×1.0	-	-	-	-	-	-	-	9.5
22120.0956	•					M12×1.5								14.0
22120.0958	•					M16×1.5								25.0
22120.0960	•					M20×1.5								27.0

Sp. 特長


- 螺牙部上拉，銷子內縮，定位解除。手放鬆後，銷子由內藏彈簧自動回位，是一種手操作的定位柱
- 螺牙部可連結配件，作其它的機構設計
- 使用溫度max.250°C

訂貨： 交期： 天

22120.0065

Ps. 備註

- 螺帽22120需另外購買

Ex. 使用例

專用扳手

