



A型
(無膠封)

B型
(有膠封)

本體		銷子		彈簧			膠封		
				輕荷重	中荷重	重荷重			
材質	顏色	材質	處理	材質	材質	處理	材質	處理	
鋁	銀	鋼	表面硬化、鍍鋅	SUS	鋼	染黑	鋼	鍍鋅	— CR

品號	備註	A	B	C	D -1	F	P(N) ≈ max.	組立棒	°C		質量 (g)	庫存
										max.		
22150.0010	鋼銷 A型(無膠封) 輕荷重	6	3	4.0	7	1.0	10	22150.0830	250		0.60	•
22150.0020		10	5	6.7	11	1.6	20	22150.0831		2.60	•	
22150.0025		10	6	10.7	11	2.0	40	22150.0831		3.40	•	
22150.0030		12	8	13.6	13	2.6	50	22150.0832		6.80	•	
22150.0040		16	10	16.7	17	3.2	100	22150.0833		14.00	•	
22150.0011	鋼銷 A型(無膠封) 中荷重	6	3	4.0	7	1.0	20	22150.0830	250		0.63	•
22150.0021		10	5	6.7	11	1.6	50	22150.0831		2.80	•	
22150.0026		10	6	10.7	11	2.0	75	22150.0831		3.60	•	
22150.0031		12	8	13.6	13	2.6	100	22150.0832		7.30	•	
22150.0041		16	10	16.7	17	3.2	150	22150.0833		15.00	•	
22150.0012	鋼銷 A型(無膠封) 重荷重	6	3	4.0	7	1.0	40	22150.0830	250		0.66	•
22150.0022		10	5	6.7	11	1.6	100	22150.0831		3.00	•	
22150.0027		10	6	10.7	11	2.0	100	22150.0831		3.90	•	
22150.0032		12	8	13.6	13	2.6	150	22150.0832		7.80	•	
22150.0042		16	10	16.7	17	3.2	200	22150.0833		15.00	•	
22150.0110	鋼銷 B型(有膠封) 輕荷重	6	3	3.7	7	1.0	10	22150.0830	110		0.60	•
22150.0120		10	5	6.0	12	1.6	20	22150.0831		2.60	•	
22150.0125		10	6	10.0	12	2.0	40	22150.0831		3.40	•	
22150.0130		12	8	13.0	14	2.6	50	22150.0832		6.90	•	
22150.0140		16	10	16.4	18	3.2	100	22150.0833		15.00	•	
22150.0111	鋼銷 B型(有膠封) 中荷重	6	3	3.7	7	1.0	20	22150.0830	110		0.60	•
22150.0121		10	5	6.0	12	1.6	50	22150.0831		2.90	•	
22150.0126		10	6	10.0	12	2.0	75	22150.0831		3.60	•	
22150.0131		12	8	13.0	14	2.6	100	22150.0832		7.50	•	
22150.0141		16	10	16.4	18	3.2	150	22150.0833		15.00	•	
22150.0112	鋼銷 B型(有膠封) 重荷重	6	3	3.7	7	1.0	40	22150.0830	110		0.70	•
22150.0122		10	5	6.0	12	1.6	100	22150.0831		3.00	•	
22150.0127		10	6	10.0	12	2.0	100	22150.0831		3.90	•	
22150.0132		12	8	13.0	14	2.6	150	22150.0832		7.90	•	
22150.0142		16	10	16.4	18	3.2	200	22150.0833		16.00	•	

Wa. 注意

- ・ P(N)是銷子移動的最大力量
- ・ 裝置方法請參考後頁

Ps. 備註

- ・ 組立工具請參考本單元

Ex. 使用例



訂貨： 交期： 天
22150.0010