



材質	顏色
PA6工程塑膠	黃

品號	適用導柱φ	A	B	H	H2	H3 ±0.1	C	Y	負載daN	庫存	單價			
NS-SSD 15	15	15.2	14.8	12	32	32	25	7	2500		•			
NS-SSD 16	16	16.2	15.8				26				•			
NS-SSD 18	18	18.2	17.8				29			2700		•		
NS-SSD 19	19	19.2	18.8				30					•		
NS-SSD 20	20	20.2	19.8				31				*	•		
NS-SSD 24	24	24.2	23.8				34		34		36	3600		•
NS-SSD 25	25	25.2	24.8								37		*	•
NS-SSD 30	30	30.2	29.8				36		36	44	4500		•	
NS-SSD 32	32	32.2	31.8							46		*	•	
NS-SSD 38	38	38.2	37.8							43		43	54	6000
NS-SSD 40	40	40.2	39.8		56			•						
NS-SSD 42	42	42.2	41.8		58		•							
NS-SSD 48	48	48.2	47.8		48	49	66	7500		•				
NS-SSD 50	50	50.2	49.8				68		*	•				
NS-SSD 52	52	52.2	51.8				70			•				
NS-SSD 60	60	60.2	59.8				52		53	79	9400	*	•	
NS-SSD 63	63	63.2	62.8		82			•						
NS-SSD 80	80	80.2	79.8		14	54		54		102		12000	*	•
NS-SSD100	100	100.2	99.8		16	56	56	123	15000	*	•			
NS-SSD125	125	125.2	124.8					150	18000	*	•			

Sp. 特長

- ・ 視覺清晰, 模具保管安全
- ・ 保管襯套負載穩定, 模具不受損
- ・ 模具開閉容易
- ・ 脫料板導柱 / 模座導柱不接觸導套和模具本體
- ・ 彈簧無模具重量負載, 模具放置平衡
- ・ 導柱、導套不損壞, 操作人員相對安全
- ・ 可加鏈條於NS-SSD上作固定
- ・ 可在本體上作攻牙

Ex. 使用例



訂貨: 交期: *記號
 NS-SSD16 其它

