


RoHS

齒輪形狀：A



TYPE	材質	處理	壓力角
HCWGT	S45C	-	20°
HCWGTT		染黑	
HCWGTH		無電解鍍	
HCWGP	SUS304	-	

標準軸孔



圓孔

TYPE	M 模數	Y 齒輪形狀	T 齒數	B 厚度	d 指定單位1mm	Dp 基準圓直徑	D 齒頂圓直徑				
(S45C) HCWGT HCWGTT HCWGTH	2.0	A	15	20	10~15	30	34				
			16		10~16	32	36				
			18		10~21	36	40				
			19			38	42				
			20		10~23	40	44				
			22		10~25	44	48				
			24		10~28	48	52				
			25			50	54				
			26		10~29	52	56				
			28		10~31	56	60				
			30		10~33	60	64				
			32			64	68				
			(SUS304) HCWGP				34		12~35	68	72
							35		12~36	70	74
36	12~38	72		76							
40	12~42	80		84							
42		84		88							
45		90		94							
48	12~43	96		100							
50		100		104							
55		110		114							

PS. 備註

- 熱處理需求歡迎洽詢
- 接受圖面詢價，可依圖面生產
- 軸孔追加加工詳細請參閱P.503

軸孔追加加工

Alteration	Code	Spec.
	AT	鍵槽孔

訂貨： TYPE - M - Y - T - B - d - (追加加工 Code)

HCWGT - 2.0 - A - 19 - 20 - 10

HCWGTH - 2.0 - A - 30 - 20 - 10 - AT

交期： 8 天 S45C

12 天 SUS304