





本體	面板	密封環
材質	材質	材質
SUS303	ESG玻璃	VITON



品號	d	d ₁	A	B	D	S	質量 (g)	庫存
SGR743.5-0010	11	M16×1.5	8	7.5	22	20	19	•
SGR743.5-0012	14	M20×1.5	8.5	7.5	26	23	23	•
SGR743.5-0014	18	M26×1.5	9	8	32	30	41	•
SGR743.5-0018	24	M33×1.5	11	8.5	40	36	64	•
SGR743.5-0022	32	M42×1.5	12	9	50	46	102	•
SGR743.5-0030	11	G3/8-19	8	7.5	22	20	19	•
SGR743.5-0032	14	G1/2-14	8.5	7.5	26	23	23	•
SGR743.5-0034	18	G3/4-14	9	8	32	30	41	•
SGR743.5-0036	24	G1-11	11	8.5	40	36	64	•
SGR743.5-0038	32	G1 1/4-11	12	9	50	46	102	•

Sp 特長

- ・油鏡可用於加壓油箱
- ・適用於負壓場合使用
- ・使用溫度max.180°C

 訂貨： 交期： 天

SGR743.5-0010

Ps 備註

- ・SGR743.5油鏡安裝在壁厚小於4mm油箱時，請參考GH螺帽
- ・依據DIN3852的規定，油鏡的外徑應與管配件的安裝孔相配

Tc 技術資料

- ・G管用平行螺牙詳細尺寸，請參考“技術資料”單元