



無通氣孔



有通氣孔



無標誌



卸油標誌



注油標誌

| | | |
|----|-----|-------|
| 本體 | 密封環 | |
| 材質 | 處理 | 材質 |
| 鋁 | 噴砂 | VITON |

| 無通氣孔 | | | | | | 有通氣孔 | | | | | |
|-------------|----|-------------|----|-------------|----|-------------|----|-------------|----|-------------|----|
| 無標誌 | | 填充標誌 | | 洩放標誌 | | 無標誌 | | 填充標誌 | | 洩放標誌 | |
| 品號 | 庫存 | 品號 | 庫存 | 品號 | 庫存 | 品號 | 庫存 | 品號 | 庫存 | 品號 | 庫存 |
| SGR742-0010 | · | SGR742-0110 | · | SGR742-0210 | · | SGR742-1010 | · | SGR742-1110 | · | SGR742-1210 | · |
| SGR742-0012 | · | SGR742-0112 | · | SGR742-0212 | · | SGR742-1012 | · | SGR742-1112 | · | SGR742-1212 | · |
| SGR742-0014 | · | SGR742-0114 | · | SGR742-0214 | · | SGR742-1014 | · | SGR742-1114 | · | SGR742-1214 | · |
| SGR742-0610 | · | SGR742-0710 | · | SGR742-0810 | · | SGR742-1610 | · | SGR742-1710 | · | SGR742-1810 | · |
| SGR742-0612 | · | SGR742-0712 | · | SGR742-0812 | · | SGR742-1612 | · | SGR742-1712 | · | SGR742-1812 | · |
| SGR742-0614 | · | SGR742-0714 | · | SGR742-0814 | · | SGR742-1614 | · | SGR742-1714 | · | SGR742-1814 | · |
| SGR742-0616 | · | SGR742-0716 | · | SGR742-0816 | · | SGR742-1616 | · | SGR742-1716 | · | SGR742-1816 | · |

| 品號 | | d ₁ | A | B | D | d | l | d ₂ | s | 質量 (g) |
|-------------|-------------|----------------|------|-----|----|----|---|----------------|----|--------|
| 無通氣孔 | 有通氣孔 | | | | | | | | | |
| SGR742-0010 | SGR742-1010 | M16×1.5 | 8.0 | 7.5 | 22 | M5 | 8 | 2 | 18 | 10 |
| SGR742-0110 | SGR742-1110 | | | | | | | | | |
| SGR742-0210 | SGR742-1210 | | | | | | | | | |
| SGR742-0012 | SGR742-1012 | M20×1.5 | 8.5 | 26 | 26 | M5 | 8 | 2 | 21 | 15 |
| SGR742-0112 | SGR742-1112 | | | | | | | | | |
| SGR742-0212 | SGR742-1212 | | | | | | | | | |
| SGR742-0014 | SGR742-1014 | M26×1.5 | 9.0 | 8.0 | 32 | M5 | 8 | 2 | 27 | 27 |
| SGR742-0114 | SGR742-1114 | | | | | | | | | |
| SGR742-0214 | SGR742-1214 | | | | | | | | | |
| SGR742-0610 | SGR742-1610 | G3/8-19 | 8.0 | 7.5 | 22 | M5 | 8 | 2 | 18 | 10 |
| SGR742-0710 | SGR742-1710 | | | | | | | | | |
| SGR742-0810 | SGR742-1810 | | | | | | | | | |
| SGR742-0612 | SGR742-1612 | G1/2-14 | 8.5 | 26 | 26 | M5 | 8 | 2 | 21 | 15 |
| SGR742-0712 | SGR742-1712 | | | | | | | | | |
| SGR742-0812 | SGR742-1812 | | | | | | | | | |
| SGR742-0614 | SGR742-1614 | G3/4-14 | 9.0 | 8.0 | 32 | M5 | 8 | 2 | 27 | 27 |
| SGR742-0714 | SGR742-1714 | | | | | | | | | |
| SGR742-0814 | SGR742-1814 | | | | | | | | | |
| SGR742-0616 | SGR742-1616 | G1-11 | 11.0 | 8.5 | 40 | M5 | 8 | 2 | 32 | 46 |
| SGR742-0716 | SGR742-1716 | | | | | | | | | |
| SGR742-0816 | SGR742-1816 | | | | | | | | | |

備註

- 油塞分為無通氣孔和有通氣孔兩種
- 使用溫度max.180°C

技術資料

- G管用平行螺牙詳細尺寸，請參考“技術資料”單元

訂貨： 交期： 天

SGR742-0010