



RoHS



Type	本體 材質	密封環 材質
100°C	鋼	NBR
180°C		VITON

工作溫度：100°C		工作溫度：180°C		d	h	s	L	D	扭緊力矩 [Nm]	質量 (g)		
品號	庫存	品號	庫存									
SGR749-0010	·	SGR749-0110	·	M10×1	8	5	12	14	10	5		
SGR749-0012	·	SGR749-0112	·	M12×1.5	12	6	17	17	20	15		
SGR749-0014	·	SGR749-0114	·	M14×1.5				19	30	20		
SGR749-0016	·	SGR749-0116	·	M16×1.5		8		22	34	25		
SGR749-0018	·	SGR749-0118	·	M18×1.5				24	42	30		
SGR749-0020	·	SGR749-0120	·	M22×1.5				10	19	27	60	50
SGR749-0022	·	-		M26×1.5	16	12	21	32	70	75		
SGR749-0024	·	-		M27×2				85	80			
SGR749-0026	·	-		M33×2		17		40	130	125		
SGR749-0028	·	SGR749-0128	·	M42×2		22		22.5	50	240	201	
SGR749-0030	·	-		M48×2		24		55	280	254		
SGR749-0210	·	SGR749-0310	·	G1/8-28		8		5	12	14	10	5
SGR749-0212	·	SGR749-0312	·	G1/4-19		12		6	17	19	26	15
SGR749-0214	·	SGR749-0314	·	G3/8-19	8		22	34	25			
SGR749-0216	·	SGR749-0316	·	G1/2-14	14	10	19	27	60	45		
SGR749-0218	·	SGR749-0318	·	G3/4-14	16	12	21	32	85	75		
SGR749-0220	·	SGR749-0320	·	G1-11		17	40	130	124			
SGR749-0222	·	SGR749-0322	·	G1 1/4-11		22	22.5	50	240	195		
SGR749-0224	·	SGR749-0324	·	G1 1/2-11		24	55	280	240			

特長

- 最大工作壓力：400 bar
- G1 1/4，G1 1/2，M42×2，M48×2最大工作壓力：250bar
- 抗拉強度：500N/mm²

 訂貨： 交期：

SGR749-0010

技術資料

- G管用平行螺牙詳細尺寸，請參考“技術資料”單元