









TYPE	材質	拉伸強度
FED□.FES□.FEG□	S45C	600N/mm <sup>2</sup> 以上
FEDS□.FESS□.FEGS□	SUS	600N/mm <sup>2</sup> 以上









L h12	公差
~10	0 -0.15
11~18	0 -0.18
19~30	0 -0.21
31~50	0 -0.25
51~80	0 -0.30
81~120	0 -0.35



FEDZ/FEDSZ

FESZ/FESSZ

FEGZ/FEGSZ



FEDY/FEDSY

FESY/FESSY

FEGY/FEGSY

TYPE	B h9	L 指定單位5mm	H h9/h11	d	d1	h	C			
FEDZ FESZ FEGZ (鋼)	8	15~80	7	3.4	6	3.5	0.25~0.40			
	10	15~80	8	4.5	7.5	4.5				
	12	20~80		5.5	9.5	5.5				
14	30~90	9								
FEDSZ FESSZ FEGSZ (不銹鋼)	15	30~90	10				6.6	11	6.5	0.40~0.60
	16	40~100								
	18	40~110	0 -0.11							

TYPE	B h9	L 指定單位5mm	H h9/h11	拔除攻牙M d	安裝用 螺栓	d1	h	C
FEDY FESY FEGY (鋼)	8	15~80	7	M4 (3.5)	M3	6	3.5	0.25~0.40
	10	15~80	8	M5 (4.3)	M4	7.5	4.5	
	12	20~80						
FEDSY FESSY FEGSY (不銹鋼)	14	30~90	9					M6 (5.3)
	15	30~90	10					
	16	40~100		11				
	18	40~110	0 -0.11					

訂貨： TYPE B - L 交期： 5 天  
FEDZ 8 - 60