



Type	把手		母牙	公牙	
	材質	顏色	材質	材質	處理
VC.192	PF (電木)	黑	黃銅	-	-
VC.192S			SUS303	-	-
VC.192P			-	鋼	鍍鉍
VC.192S-P	-	-	SUS303	-	-

黃銅 品號	質量 (g)	庫存	不銹鋼 品號	質量 (g)	庫存	A	B	C	D	E	F
VC.192-010	11	•	-	-	-	25	21	15	9	M4×0.7	10
VC.192-012	16	•	-	-	-	32	23	19	11	M5×0.8	
VC.192-014	19	•	VC.192S-114	18	•					40	27
VC.192-016	27	•	-	-	-	50	33	25	14		
VC.192-018	31	•	VC.192S-118	30	•					60	37
VC.192-020	50	•	-	-	-	70	44	30	20		
VC.192-022	52	•	VC.192S-122	50	•					85	55
VC.192-024	76	•	-	-	-						
VC.192-026	80	•	VC.192S-126	78	•						
VC.192-028	119	•	-	-	-						
VC.192-030	176	•	-	-	-						

鋼 品號	質量 (g)	庫存	不銹鋼 品號	質量 (g)	庫存	A	B	C	D	E	F											
VC.192P-210	11	•	-	-	-	25	21	15	9	M5×0.8	10											
VC.192P-212	12	•								M6×1	16											
VC.192P-214	10	•									10											
VC.192P-216	12	•								16												
VC.192P-218	14	•								20												
VC.192P-220	18	•								30												
VC.192P-224	17	•								VC.192S-P-324	17	•	32	23	19	11	M8×1.25	10				
VC.192P-226	18	•								VC.192S-P-326	18	•						M6×1	16			
VC.192P-228	20	•								VC.192S-P-328	20	•					40		27	21	12	M8×1.25
VC.192P-230	25	•								VC.192S-P-330	25	•						50				
VC.192P-232	24	•	-	-	-	M8×1.25	20															
VC.192P-234	27	•					M6×1	30														
VC.192P-236	29	•				40																
VC.192P-238	30	•				20																
VC.192P-240	32	•				30																
VC.192P-242	35	•				16																
-	-	-				VC.192S-P-344	36	•	40	27	21	12	M8×1.25	20								
VC.192P-246	38	•				VC.192S-P-346	38	•						M6×1	25							
-	-	-				VC.192S-P-348	39	•					50		33	25	14	M8×1.25	30			
VC.192P-250	40	•				VC.192S-P-350	40	•						M10×1.5					35			
VC.192P-252	43	•	VC.192S-P-352	43	•	60	37	27					17		M12×1.75	45						
VC.192P-254	52	•	-	-	-									M6×1		16						
VC.192P-256	53	•				M8×1.25	20															
VC.192P-258	55	•					M10×1.5	25														
VC.192P-260	56	•				M12×1.75		30														
VC.192P-262	60	•					M6×1	40														
VC.192P-264	63	•				VC.192S-P-364		63	•	50	33	25	14	M8×1.25	20							
VC.192P-266	66	•				VC.192S-P-366	66	•	M10×1.5						30							
VC.192P-268	70	•				VC.192S-P-368	70	•		60	37	27	17	M12×1.75	40							
VC.192P-270	73	•				VC.192S-P-370	73	•	M6×1						50							
VC.192P-272	87	•				-	-	-		M8×1.25	20											
VC.192P-274	92	•	M10×1.5	30																		
VC.192P-276	98	•		M12×1.75	40																	
VC.192P-278	101	•	M6×1		50																	
VC.192P-280	105	•		M8×1.25	25																	
VC.192P-282	110	•	VC.192S-P-382		110				•	50	33	25	14	M10×1.5	30							
VC.192P-284	118	•	VC.192S-P-384	118	•				M12×1.75						40							
VC.192P-286	128	•	VC.192S-P-386	128	•																	

Sp. 特長

· 本產品耐各種溶劑，耐油性和耐化學性...等

Te. 技術資料

· 使用溫度max.110°C，min.-20°C

訂貨：  交期：

VC.192-010