



RoHS SUS



WWY
WUY (不銹鋼)



TWY
TUY (不銹鋼)



Type	材質
WWY TWY	SWP
WUY TUY	SUS304

· 輕荷重型 *符號僅限於WWY · WUY

品號 Type	D-L	線徑 d	動荷重的情況		初張力 N	定數 N/mm	庫 存	
			最大 拉伸量 Fmax. mm	最大 荷重 N			WWY WUY	TWY TUY
WWY WUY	2-10	0.25	5.7	1.86	0.34	0.27	·	·
			10.3			0.15	·	·
			14.0			0.11	·	·
			18.2			0.08	·	·
			22.1			0.07	·	·
WWY TWY WUY TUY	3-10	0.3	8.7	2.25	0.29	0.23	·	·
			16.6			0.12	·	·
			25.0			0.08	·	·
			33.3			0.06	·	·
WWY TWY WUY TUY	4-15	0.4	10.0	3.24	0.59	0.26	·	·
			16.8			0.16	·	·
			22.5			0.12	·	·
			28.4			0.09	·	·
WWY TWY WUY TUY	5-15	0.5	6.8	4.22	0.88	0.49	·	·
			11.7			0.28	·	·
			17.0			0.20	·	·
			21.2			0.16	·	·
			26.1			0.13	·	·
			34.0			0.10	·	·
WWY TWY WUY TUY	6-25	0.6	14.0	8.14	1.27	0.49	·	·
			21.2			0.32	·	·
			28.0			0.25	·	·
			35.0			0.20	·	·
			41.1			0.17	·	·
			50.0			0.14	·	·
			53.8			0.13	·	·
63.6	0.11	·	·					
WWY TWY WUY TUY	8-25	0.8	15.1	12.75	2.35	0.69	·	·
			21.2			0.49	·	·
			26.5			0.39	·	·
			33.1			0.31	·	·
			39.2			0.26	·	·
			46.0			0.23	·	·
			53.0			0.22	·	·
			58.8			0.20	·	·
66.2	0.18	·	·					
WWY TWY WUY TUY	10-30	1.0	11.5	15.00	3.73	0.98	·	·
			15.3			0.74	·	·
			19.8			0.57	·	·
			23.9			0.47	·	·
			28.7			0.39	·	·
			32.8			0.34	·	·
			37.0			0.30	·	·
			39.6			0.29	·	·
			44.2			0.26	·	·
			47.9			0.24	·	·
*符號僅 限WWY WUY	*90 *100		52.2			0.22	·	·
			60.5			0.19	·	-
			71.8			0.16	·	-

品號 Type	D-L	線徑 d	動荷重的情況		初張力 N	定數 N/mm	庫 存	
			最大 拉伸量 Fmax. mm	最大 荷重 N			WWY WUY	TWY TUY
WWY TWY WUY TUY	12-35	1.2	22.0	31.37	5.39	1.18	·	·
			27.8			0.93	·	·
			35.3			0.74	·	·
			42.0			0.62	·	·
			50.0			0.52	·	·
			55.2			0.47	·	·
			63.0			0.41	·	·
			69.7			0.37	·	·
			77.9			0.33	·	·
			82.8			0.31	·	·
WWY WUY	14-40	1.5	15.4	38.24	8.43	1.94	·	·
			21.0			1.42	·	·
			25.4			1.17	·	·
			30.8			0.97	·	·
			37.0			0.8	·	·
			43.2			0.69	·	·
			46.2			0.64	·	·
			52.8			0.56	·	·
			58.3			0.51	·	·
			68.1			0.43	·	·
WWY WUY	16-45	1.6 (WWY) 1.7 (WUY)	15.8	43.15	9.12	2.16	·	·
			21.0			1.62	·	·
			25.7			1.32	·	·
			31.5			1.08	·	·
			35.8			0.95	·	·
			40.8			0.83	·	·
			46.3			0.74	·	·
			49.6			0.69	·	·
			60.9			0.56	·	·
			69.4			0.49	·	·
WWY	18-50	1.8	21.0	52.96	9.81	2.05	·	·
			26.0			1.66	·	·
			31.0			1.39	·	·
			36.0			1.20	·	·
			42.0			1.03	·	·
			46.0			0.94	·	·
			54.0			0.80	·	·
			66.0			0.65	·	·
			75.0			0.58	·	·
			104.5			0.41	·	·
WWY	20-60	2.0	29.1	78.45	12.75	2.26	·	·
			41.8			1.57	·	·
			53.6			1.23	·	·
			67.0			0.98	·	·
			78.8			0.83	·	·
			111.6			0.59	·	·
			139.5			0.47	·	·
			167.5			0.39	·	·

PS) 備註

· 拉伸彈簧支柱溝槽型TSPO/STSP0, 圓孔型WSPO/SWSP0
WIPO/SWIPO詳細規格, 請至伍全官網

訂貨: 交期: 天

WWY2-10