







I.280



I.580N



Type	材質	顏色
I.280	PF(電木)	黑
I.580N	PP	霧黑

品號	A	B	C	D	E	F	G	質量 (g)	庫存
I.280-010	28	14	11	5.5	M5×0.8	12	1.5	5	•
I.280-020	40	18	15	6.5	M6×1	25	3.5	12	•
I.280-030				8.5	M8×1.25			21	•
I.280-040	50	21	17	6.5	M6×1	35	7.5	20	•
I.280-050				8.5	M8×1.25			30	33
I.280-060	65	23	19	10.5	M10×1.5	40	7.0	30	•
I.280-070						55		47	•
I.280-080	80	26	21	12.5	M12×1.75	55	10.0	45	•
I.280-090							7.0	64	•
I.280-100	90	28	22	10.5	M10×1.5	58	8.0	62	•
I.280-110								90	90
I.280-120	102	31	25	12.5	M12×1.75	58	8.0	88	•
I.280-130	116	29	23						•

Sp. 特長

· 以螺牙組配

Te. 技術資料

· 使用溫度max.110°C，min.-20°C

訂貨： 交期：

I.280-010

品號	A	B	C	D	E	質量 (g)	庫存
I.580N-010	40	18	15	8	28	8	•
I.580N-020	50	21	17	10	35	10	•
I.580N-030					45	17	•
I.580N-040	65	23	19	12	45	16	•
I.580N-050						25	•
I.580N-060	80	26	21	14	50	24	•
I.580N-070						33	•
I.580N-080	90	28	22	15	60	32	•
				16		•	

Sp. 特長

· 以標準磨光棒(公差h9)壓入組配即可
 · I.280材質是PF，I.580N材質是PP，耐各種溶劑及耐油和耐化學性…等

Te. 技術資料

· 使用溫度max.80°C，min.0°C

訂貨： 交期：

I.580N-010