



Type	橡膠 材質	華司 材質
SPCW	NBR	SPCC
SUSW	NBR	SUS304
SPCW-F	FKM	SPCC

① 一般用				② 高溫 · 藥品用				適用稱呼 尺寸		密封墊華司 稱呼尺寸				最大鎖緊 力矩 kgf.cm
墊圈：NBR		墊圈：NBR		墊圈：FKM		螺栓	孔徑	d	D	D ₁	T			
華司：SPCC		華司：SUS304		華司：SPCC										
品號	庫存	品號	庫存	品號	庫存									
SPCW-2.6		SUSW-2.6	△	SPCW-2.6F		M2.6	3	2.4	8.5	5.5	1.2	-		
SPCW-3		SUSW-3		SPCW-3F		M3	3.4	2.8	10	6	1.2			
SPCW-4		SUSW-4	△	SPCW-4F	△	M4	4.5	3.8	11	7	1.2			
SPCW-5		SUSW-5		SPCW-5F		M5	5.5	4.8	12	8	1.2			
SPCW-6		SUSW-6	△	SPCW-6F	△	M6	6.6	5.8	13	9	1.2		34	
SPCW-8		SUSW-8	△	SPCW-8F	△	M8	9	7.8	16	12	1.2		66	
SPCW-10		SUSW-10	△	SPCW-10F	△	M10	11	9.8	18	14	1.2		360	
SPCW-12		SUSW-12	△	SPCW-12F	△	M12	13.5	11.8	22	16	1.2		510	
SPCW-14		SUSW-14	△	SPCW-14F	△	M14	15.5	13.8	23	18	1.2		900	
SPCW-16		SUSW-16	△	SPCW-16F	△	M16	17.5	15.8	27	20	1.2		1230	
SPCW-18		SUSW-18	△	-		M18	20	17.8	28	22	1.2	1810		
SPCW-20		SUSW-20	△	SPCW-20F	△	M20	22	19.8	32	24	1.2	2820		
SPCW-22	△	SUSW-22	△	SPCW-22F	△	M22	24	21.75	35	27	1.6(1.5)	2890		
SPCW-24	△	SUSW-24	△	SPCW-24F	△	M24	26	23.75	39	29	1.6(1.6)	4850		
SPCW-25		SUSW-25	△	-		M25	27	24.75	36	29	1.2	-		
SPCW-28	△	SUSW-28		SPCW-28F	△	M28	31	27.75	42	33	1.6(1.6)			
SPCW-30	△	SUSW-30	△	SPCW-30F	△	M30	33	29.75	48	35	1.6(1.6)	11400		
SPCW-36	△	SUSW-36	△	SPCW-36F		M36	39	35.75	56	41	1.6(1.6)	19730		
SPCW-38	△	SUSW-38		SPCW-38F		M38	41	37.75	60	43	1.6(1.6)	-		
SPCW-42	△	-		-		M42	45	41.7	65	48	2	53090		
SPCW-48	△	SUSW-48		SPCW-48F		M48	52	47.7	73	54	2	77670		

Sp. 特長

- 上表是標準 Type I
- 密封墊華司在橡膠不受損情況下，可以重複使用

Wa. 注意

- 請勿將密封墊華司放置於日光直射或溫度高於40°C以上場所，最好收藏在陰暗處
- 組立時，橡膠部不能刮傷
- 密封墊華司最好在兩年內使用之
- 密封墊華司缺貨時，交期較長或有最小訂貨量規定

訂貨： 交期： 天 · 天 △
SPCW-2.6

Ex. 使用例

