



RoHS



材質	處理
EN 1.7182	硬化+ Delta Protekt

品號	螺栓尺寸		Ø1	Ø0	T	品號	螺栓尺寸		Ø1	Ø0	T	
	公制	UNC					公制	UNC				
NORD-NL3	M3	#5	3.4	7.0	1.8	NORD-NL24	M24		25.3	39.0	±0.2	3.4
NORD-NL3.5	M3.5	#6	3.9	7.6		NORD-NL24SP						48.5
NORD-NL3.5SP							9.0	NORD-NL1		1"	27.9	
NORD-NL4	M4	#8	4.4	7.6		NORD-NL1SP					48.5	4.6
NORD-NL4SP							9.0	NORD-NL27	M27			28.4
NORD-NL5	M5	#10	5.4	10.8		NORD-NL27SP					48.5	
NORD-NL5SP							±0.1		M30	1 1/8"	31.4	±0.2
NORD-NL6	M6		6.5	13.5		NORD-NL30SP					58.5	±0.3
NORD-NL6SP						11.5	NORD-NL33	M33	1 1/4"	34.4		48.5
NORD-NL1-4		1/4"	7.2	13.5		NORD-NL33SP					58.5	6.6
NORD-NL1-4SP				16.6	NORD-NL36	M36	1 3/8"	37.4		55.0	5.8	
NORD-NL8	M8	5/16"	8.7	21.0	NORD-NL36SP					63.0	6.6	
NORD-NL8SP					16.6	NORD-NL39	M39	1 1/2"	40.4		58.5	5.8
NORD-NL3-8		3/8"	10.3	±0.2	NORD-NL42	M42		43.2		63.0		
NORD-NL3-8SP				16.6	NORD-NL45	M45	1 3/4"	46.2		70.0	7.0	
NORD-NL10	M10		10.7	21.0	NORD-NL48	M48		49.6		75.0		
NORD-NL10SP					18.5	NORD-NL52	M52	2"	53.6			80.0
NORD-NL11	M11	7/16"	11.4	19.5	NORD-NL56	M56	2 1/4"	59.1		85.0		
NORD-NL12	M12		13.0	25.4	NORD-NL60	M60		63.1		90.0		
NORD-NL12SP					19.5	NORD-NL64	M64	2 1/2"	67.1			95.0
NORD-NL1-2		1/2"	13.5	25.4	NORD-NL68	M68		71.1		100.0		
NORD-NL1-2SP				23.0	NORD-NL72	M72		75.1		105.0		
NORD-NL14	M14	9/16"	15.2	30.7	NORD-NL76	M76	3"	79.1		110.0		
NORD-NL14SP					±0.2	NORD-NL80	M80	3 1/8"	83.1	+0.5 -0.0		+0.0 -2.0
NORD-NL16	M16	5/8"	17.0	25.4	NORD-NL85	M85		88.1		115.0		
NORD-NL16SP					30.7	NORD-NL90	M90		92.4		120.0	
NORD-NL18	M18		19.5	29.0	NORD-NL95	M95		97.4		130.0		
NORD-NL18SP					34.5	NORD-NL100	M100	4"	103.4		135.0	
NORD-NL3-4		3/4"	20.0	30.7	NORD-NL105	M105		108.4		145.0		
NORD-NL3-4SP				39.0	NORD-NL110	M110		113.4		150.0		
NORD-NL20	M20		21.4	30.7	NORD-NL115	M115		118.4		165.0		
NORD-NL20SP					39.0	NORD-NL120	M120		123.4		170.0	
NORD-NL22	M22	7/8"	23.4	34.5	NORD-NL125	M125		128.4		173.0		
NORD-NL22SP					42.0	NORD-NL130	M130	5"	133.4		178.0	

Ex. 使用例



螺孔



穿通孔



埋頭孔



螺樁



大孔/槽孔



不建議使用 Nord-Lock 墊圈的設計

- 配合面未鎖固定位
- 配合面比墊圈還硬
- 配合面非常軟，如木頭、塑膠
- 大規模沉陷的應用
- 無預加負荷的接頭

訂貨： 交期： 天 ≤M20
 天 ≥M22

Wa. 注意

- T = 6.6厚度許可公差是+0/-0.5
- 此產品交期缺貨時較長，請儘早訂貨