



RoHS SUS



材質	處理
鋼	熱處理
SUS304	

品號	備註	A	B	S	h max.	適用螺栓		庫存			
						mm	inch	鋼	SUS304		
S1.6	-	1.7	3.2	0.35	0.6	1.6	-	·			
S2	-	2.2	4.0			2.0					
S2.5	-	2.7	4.8			2.5					
S3	SS3	3.2	5.5	0.45	0.9	3.0	1/8"	·	·		
S3.5	-	3.7	6.0			3.5	-				
S4	SS4	4.3	7.0			4.0	5/32"		·	·	
S5	SS5	5.3	9.0	5.0	3/16"	·					
S6	SS6	6.4	10.0	6.0	-	·					
S6.35	-	6.7	9.5	0.7	1.2	-	1/4"	·			
S7	-	7.4	12.0			1.3	7.0		-		
S8	SS8	8.4	13.0			1.4	8.0		5/16"	·	·
S10	SS10	10.5	16.0	1.0	1.6	10.0	3/8"	·	·		
S11.1	-	11.6	15.9			-	7/16"		·	·	
S12	SS12	13.0	18.0			1.1	1.7			12.0	-
S12.7	-	13.7	19.0	1.8	-	1/2"	·				
S14	-	15.0	22.0	1.2	2.0	14.0	-	·			
S16	SS16	17.0	24.0	1.3	2.1	16.0	5/8"	·	△		
S18	-	19.0	27.0	1.5	2.3	18.0	-	·			
S19	-	20.0	30.0			-	3/4"		·		
S20	SS20	21.0	30.0			2.4	20.0			-	△
S22	-	23.0	33.0	1.8	2.5	22.0	7/8"	·			
S24	SS24	25.6	36.0			2.7	24.0		-	△	
S25.4	-	27.0	38.0			2.8	-		1"	·	
S27	-	28.6	39.0	2.0	2.9	27.0	-	·			
S30	SS30	31.6	45.0			3.2	30.0		1 1/8"	·	△
S36	-	38.0	54.0			2.5	4.0		36.0	1 3/8"	·
VS5	VSS5	5.3	9.0	1.0	1.3	5.0	3/16"	·	·		
VS6	VSS6	6.4	10.0			1.4	6.0		-	·	·
VS8	VSS8	8.4	13.0	1.2	1.7	8.0	5/16"	·	·		
VS10	VSS10	10.5	16.0			2.0	10.0		3/8"	·	·
VS12	VSS12	13.0	18.0			1.5	2.1		12.0	-	·
VS14	-	15.0	22.0	2.2	14.0			-	·		
VS16	VSS16	17.0	24.0	2.6	16.0			5/8"	·	△	
VS18	-	19.0	27.0	2.0	2.7	18.0	-	·			
VS20	VSS20	21.0	30.0			2.8	20.0		-	△	
VS22	-	23.0	33.0			2.9	22.0		7/8"	·	
VS24	VSS24	25.6	36.0	2.5	3.3	24.0	-	·	△		
VS27	-	28.6	39.0			3.4	27.0		-	·	
VS30	VSS30	31.6	45.0			3.6	30.0		1 1/8"	·	△

訂貨：  交期：  天 ·  
S1.6  △