



[RoHS](#) [SUS](#) [EN](#)

T	LBSNP公差	材質	T	D-DIP-A公差	材質
0.05	± 0.005	SUS304	0.05	± 0.003	SUS301
0.1	± 0.02		0.06	± 0.004	
0.2	± 0.03		0.07	± 0.004	
0.3	± 0.035		0.08	± 0.004	
0.5	± 0.04		0.09	± 0.004	
1	± 0.05		0.1	± 0.02	
			0.2		
			0.3		
			0.5		
			1		


D=45 · 55(1孔)



D=80(2孔)



D=65 · 80×3 · 90(3孔)



品號 Type	D	T	安裝 孔數	庫存	品號 Type	D	T	安裝 孔數	庫存	品號 Type	D	T	安裝 孔數	庫存
LBSNP	45	0.05	1	.	LBSNP	65	0.05	3	.	D-DIP-A	65	0.05	.	.
		0.1		.			0.1		.			0.06	.	.
		0.2		.			0.2		.			0.07	.	.
		0.3		.			0.3		.			0.08	.	.
		0.5		.			0.5		.			0.09		.
	55	1		.		80×3	0.05	.	.			0.1	.	.
		0.05		.			0.1		.			0.2	.	.
		0.1		.			0.2		.			0.3	.	.
		0.2		.			0.3		.			0.5		.
		0.3		.			0.5		.			1	3	.
LBSNP	80	0.5	2	.		90	0.05	.	.			0.05	.	.
		0.1		.			0.1		.			0.06	.	.
		0.2		.			0.2		.			0.07	.	.
		0.3		.			0.3		.			0.08		.
		0.5		.			0.5		.			0.09	.	.
		1		.			1		.			0.1	.	.
												0.2		.

Sp. 特長

- 厚度公差嚴格控管
- 產品上標示厚度、長度和寬度，節省量測時間，作業效率提升

訂貨 : 品號 D - T 交期 : 1 天

LBSNP 55 - 0.05

D-DIP-A 65 - 0.05

LBSNP 80×3 - 0.05