



**(RoHS) SUS**



d · D	d公差	D公差
2~50	+0.2 0	0 -0.2
50.1~200	+0.5 0	0 -0.5
200.1~250	+0.7 0	0 -0.7

#### 製作條件

外徑 $\varnothing$ 4~50時，  
T0.05~0.3 … K≥1  
T0.35~6 … K≥2  
外徑 $\varnothing$ 50.1~250時，  
T0.05~2 … K≥2  
T2.3~4 … K≥T, d≥3或d=0  
T4.5~6 … K≥T, d≥4或d=0

#### 硬化鋼

T0.35, 0.7, 1.2~2…D≤80

Type	材質	T											
		0.05	0.1	0.15	0.2	0.25	0.3	0.35	0.4	0.5	0.6	0.7	0.8
FRF	鐵(T0.1~3: ≈SPCC、T3.2~6: SPHC)	-	±0.03	±0.03	±0.03	±0.04	±0.04	-	±0.05	±0.05	±0.06	-	±0.06 ±0.08
FRY	硬化鋼(T0.1~0.15: SK95、T0.2~2: SK85) …硬度HRC42~46	-	±0.015	±0.015	±0.02	±0.025	±0.025	±0.025	±0.035	±0.035	±0.04	±0.04	±0.04 ±0.05
FRS	不銹鋼(SUS304)	±0.005	±0.008	±0.008	±0.01	±0.015	±0.015	±0.015	±0.02	±0.02	±0.025	±0.03	±0.03 ±0.035
FRB	黃銅(C2680或C2801)	±0.005	±0.02	±0.02	±0.02	±0.02	±0.03	-	±0.04	±0.04	±0.04	±0.04	±0.04 ±0.05
FRC	銅(T0.1: C1020、T0.15~1: C1100)	-	±0.02	±0.02	±0.02	±0.02	±0.03	-	±0.04	±0.04	±0.04	±0.04	±0.04 ±0.05
FRA	鋁(T0.1~0.15: 1N30、T0.2~3: A1050)	-	±0.03	±0.03	±0.03	-	±0.04	-	±0.04	±0.04	-	±0.05	±0.05 ±0.05

Type	材質	T												
		1.2	1.5	1.6	2	2.3	2.5	2.6	3	3.2	4	4.5	5	6
FRF	鐵(T0.1~3: ≈SPCC、T3.2~6: SPHC)	±0.08	-	±0.12	±0.14	±0.14	-	±0.21	±0.23	±0.23	±0.26	±0.26	±0.28	±0.3
FRY	硬化鋼(T0.1~0.15: SK95、T0.2~2: SK85) …硬度HRC42~46	±0.05	±0.05	±0.06	±0.07	-	-	-	-	-	-	-	-	-
FRS	不銹鋼(SUS304)	±0.1	±0.12	-	±0.17	-	±0.22	-	±0.22	-	±0.35	-	±0.4	±0.5
FRB	黃銅(C2680或C2801)	±0.05	±0.06	-	±0.06	-	-	-	-	-	-	-	-	-
FRC	銅(T0.1: C1020、T0.15~1: C1100)	-	-	-	-	-	-	-	-	-	-	-	-	-
FRA	鋁(T0.1~0.15: 1N30、T0.2~3: A1050)	±0.06	±0.06	-	±0.08	-	-	-	±0.11	-	-	-	-	-

Type	指定單位: 0.1mm ※銅: 1 mm		T*	庫存							
	d	D		鐵	硬化鋼	不銹鋼	黃銅	銅	鋁		
				FRF	FRY	FRS	FRB	FRC	FRA		
FRF (鐵)	4~20	0 (無孔)	0.05			△	△				
			0.1~0.5	△	△	△	△	△	△		
			0.6~1	△	△	△	△	△	△		
			1.2~2.3	△	△	△	△				
			2.5~3.2	△		△					
			4~4.5	△		△					
FRY (硬化鋼)	2~	20.1~50	5~6	△		△					
			0.05			△	△				
			0.1~0.5	△	△	△	△	△	△		
			0.6~1	△	△	△	△	△	△		
			1.2~2.3	△	△	△	△				
			2.5~3.2	△		△					
FRS (不銹鋼)	0 (無孔)	4~4.5	4~4.5	△		△					
			5~6	△		△					
			0.05			△	△				
			0.1~0.5	△	△	△	△	△	△		
			0.6~1	△	△	△	△	△	△		
			1.2~2.3	△	△	△	△				
FRB (黃銅)	2~	20.1~50	2.5~3.2	△		△					
			4~4.5	△		△					
			5~6	△		△					
			0.05			△	△				
			0.1~0.5	△	△	△	△	△	△		
			0.6~1	△	△	△	△	△	△		
FRC (銅)	2~	20.1~50	1.2~2.3	△	△	△	△				
			2.5~3.2	△		△					
			4~4.5	△		△					
			5~6	△		△					
			0.05			△	△				
			0.1~0.5	△	△	△	△	△	△		
FRA (鋁)	2~	20.1~50	0.6~1	△	△	△	△	△	△		
			1.2~2.3	△	△	△	△				
			2.5~3.2	△		△					
			4~4.5	△		△					
			5~6	△		△					
			0.05			△	△				

#### PS. 備註

· 尺寸指定時，請注意製作條件

· \*規格請參照厚度公差表

Type	指定單位：0.1mm ※銅：1 mm		T*	庫存						
	d	D		鐵	硬化鋼	不銹鋼	黃銅	銅	鋁	
				FRF	FRY	FRS	FRB	FRC	FRA	
FRF (鐵)	50.1~100	0	0.05			△	△			
			0.1~0.5	△	△	△	△		△	
			0.6~1	△	△	△	△		△	
			1.2~2.3	△	△	△	△		△	
			2.5~3.2	△		△			△	
			4、4.5	△		△				
	100.1~150		5、6	△		△				
	0	0.05			△	△				
		0.1~0.5	△		△	△		△		
		0.6~1	△		△	△		△		
		1.2~2.3	△		△	△		△		
		2.5~3.2	△		△			△		
	150.1~200	2~	4、4.5	△		△				
			5、6	△		△				
			0.05			△	△			
			0.1~0.5	△		△	△		△	
			0.6~1	△		△	△		△	
			1.2~2.3	△		△	△		△	
	200.1~250		2.5~3.2	△		△			△	
			4、4.5	△		△				
			5、6	△		△				

**PS. 備註**

- 尺寸指定時，請注意製作條件
- \* 規格請參照厚度公差表

訂貨 : Type -  d -  D -  T - 處理交期 :  20 天

FRF - 2 - 4 - 0.05

FRF - 2 - 4 - 0.05 - LM

**處理**

- 雷射刻字 ……品號末尾 LM
- 蓋印 ……品號末尾 S
- 黏著劑塗布 ……品號末尾 N
- 染黑 ……品號末尾 C