


RoHS SUS



$d \cdot D \cdot b \cdot h$	$d \cdot h$ 公差	D公差	b公差
2~50	+0.2 0	0 -0.2	
50.1~200	+0.5 0	0 -0.5	+0.5 0
200.1~250	+0.7 0	0 -0.7	

## 製作條件

$K \geq 2$   
 $h > d$   
硬化鋼  
 $T_{0.35}, 0.7, 1.2 \sim 2 \cdots D \leq 80$

Type	材質	T												
		0.05	0.1	0.15	0.2	0.25	0.3	0.35	0.4	0.5	0.6	0.7	0.8	1
FKF	鐵(T0.1~3:≈SPCC、T3.2~6:SPHC)	-	±0.03	±0.03	±0.03	±0.04	±0.04	-	±0.05	±0.05	±0.06	-	±0.06	±0.08
FKY	硬化鋼(T0.1~0.15:SK95、T0.2~2:SK85) ...硬度HRC42~46	-	±0.015	±0.015	±0.02	±0.025	±0.025	±0.025	±0.035	±0.035	±0.04	±0.04	±0.04	±0.05
FKS	不銹鋼(SUS304)	±0.005	±0.008	±0.008	±0.01	±0.015	±0.015	±0.015	±0.02	±0.02	±0.025	±0.03	±0.03	±0.035
FKB	黃銅(C2680或C2801)	±0.005	±0.02	±0.02	±0.02	±0.02	±0.03	-	±0.04	±0.04	±0.04	±0.04	±0.04	±0.05
FKA	鋁(T0.1~0.15:1N30、T0.2~3:A1050)	-	±0.03	±0.03	±0.03	-	±0.04	-	±0.04	±0.04	±0.04	-	±0.05	±0.05

Type	材質	T												
		1.2	1.5	1.6	2	2.3	2.5	2.6	3	3.2	4	4.5	5	6
FKF	鐵(T0.1~3:≈SPCC、T3.2~6:SPHC)	±0.08	-	±0.12	±0.14	±0.14	-	±0.21	±0.23	±0.23	±0.26	±0.26	±0.28	±0.3
FKY	硬化鋼(T0.1~0.15:SK95、T0.2~2:SK85) ...硬度HRC42~46	±0.05	±0.05	±0.06	±0.07	-	-	-	-	-	-	-	-	-
FKS	不銹鋼(SUS304)	±0.1	±0.12	-	±0.17	-	±0.22	-	±0.22	-	±0.35	-	±0.4	±0.5
FKB	黃銅(C2680或C2801)	±0.05	±0.06	-	±0.06	-	-	-	-	-	-	-	-	-
FKA	鋁(T0.1~0.15:1N30、T0.2~3:A1050)	±0.06	±0.06	-	±0.08	-	-	-	±0.11	-	-	-	-	-

Type	指定單位 : 0.1mm				板厚 T*	庫存						
	內徑 d	外徑 D	鍵寬 b	鍵高 h		鐵	硬化鋼	SUS	黃銅	鋁		
						FKF	FKY	FKS	FKB	FKA		
FKF (鐵)	13~20	2~	7~	0.05				△	△			
				0.1~0.5		△	△	△	△	△		
				0.6~1		△	△	△	△	△		
	20.1~50			1.2~2.3		△	△	△	△	△		
				2.5~3.2		△		△		△		
				4~4.5		△		△				
FKY (硬化鋼)	6~			5~6		△		△				
				0.05			△	△				
				0.1~0.5		△	△	△	△	△		
	20.1~50			0.6~1		△	△	△	△	△		
				1.2~2.3		△	△	△	△	△		
				2.5~3.2		△		△		△		
FKS (SUS)	6~			4~4.5		△		△				
				5~6		△		△				
				0.05			△	△				
	20.1~50			0.1~0.5		△	△	△	△	△		
				0.6~1		△	△	△	△	△		
				1.2~2.3		△	△	△	△	△		
FKB (黃銅)	6~			2.5~3.2		△		△				
				4~4.5		△		△				
				5~6		△		△				
	20.1~50			0.05			△	△				
				0.1~0.5		△	△	△	△	△		
				0.6~1		△	△	△	△	△		
FKA (鋁)	6~			1.2~2.3		△	△	△	△	△		
				2.5~3.2		△		△				
				4~4.5		△		△				
	20.1~50			5~6		△		△				
				0.05			△	△				
				0.1~0.5		△	△	△	△	△		

## PS. 備註

- 尺寸指定時，請注意製作條件
- \* 規格請參照厚度公差表

Type	指定單位：0.1mm				板厚 T*	庫存					
	內徑 d	外徑 D	鍵寬 b	鍵高 h		鐵	硬化鋼	SUS	黃銅	鋁	
						FKF	FKY	FKS	FKB	FKA	
FKF (鐵)	50.1~100	6~	2~	7~	0.05			△	△		
					0.1~0.5	△	△	△	△	△	
					0.6~1	△	△	△	△	△	
					1.2~2.3	△	△	△	△	△	
					2.5~3.2	△		△		△	
					4、4.5	△		△			
					5、6	△		△			
					0.05			△	△		
					0.1~0.5	△		△	△	△	
FKY (硬化鋼)	100.1~150	6~	2~	7~	0.6~1	△		△	△	△	
					1.2~2.3	△		△	△	△	
					2.5~3.2	△		△		△	
					4、4.5	△		△			
					5、6	△		△			
					0.05			△	△		
	150.1~200	6~	2~	7~	0.1~0.5	△		△	△	△	
					0.6~1	△		△	△	△	
					1.2~2.3	△		△	△	△	
					2.5~3.2	△		△		△	
					4、4.5	△		△			
					5、6	△		△			
FKS (SUS)	200.1~250	6~	2~	7~	0.05			△	△		
					0.1~0.5	△		△	△	△	
					0.6~1	△		△	△	△	
					1.2~2.3	△		△	△	△	
					2.5~3.2	△		△		△	
					4、4.5	△		△			
					5、6	△		△			
					0.05			△	△		
					0.1~0.5	△		△	△	△	
					0.6~1	△		△	△	△	
					1.2~2.3	△		△	△	△	

**PS. 備註**

- 尺寸指定時，請注意製作條件
- \* 規格請參照厚度公差表

訂貨 : Type - d - D - b - h - T - 處理 交期 : 20 天

FKS - 25 - 40 - 8.5 - 28.5 - 1

FKS - 25 - 40 - 8.5 - 28.5 - 1 - LM

**處理**

- 雷射刻字 ……品號末尾 LM
- 蓋印 ……品號末尾 S
- 黏著劑塗布 ……品號末尾 N
- 染黑 ……品號末尾 C