



本體	顏色	螺栓	
		材質	處理
NR(橡膠)	黑	SS400	鍍鋅
		SUS304	-

品 號				D	L	d	C	最大荷重 (N)	最大壓縮量 (mm)	硬度 (Shore A)	質 量 (g)
鋼	庫存	不銹鋼	庫存								
FVG-416301	·	-		20	24	M6×1	6	82	6	40	8
FVG-413601	·	FVG-410601	·					130		55	
FVG-419001	·	-						330		70	
FVG-416311	·	-		30	30	M8×1.25	8	190	7.5	40	28
FVG-413611	·	FVG-410611	·					260		55	
FVG-419011	·	-						630		70	
FVG-416321	·	-		30	36	M8×1.25	8	180	9	40	30
FVG-413621	·	FVG-410613	·					320		55	
FVG-419021	·	-						650		70	
FVG-416331	·	-		35	40	M8×1.25	8	260	10	40	43
FVG-413631	·	FVG-410621	·					300		55	
FVG-419031	·	-						630		70	
FVG-413641	·	-		50	61	M10×1.5	10	600	15.25	55	114
FVG-416351	·	-						490		40	
FVG-413651	·	-						890		55	
FVG-419051	·	-		50	68	M10×1.5	10	1950	17	70	120

Sp. 特長

- 用在減震和降低機件的晃動及噪音

Ex. 使用例

訂貨： 交期：

FVG-416301

Ps. 備註

- 1N=0.101972kgf
- 荷重 (N) = 定數 (N/mm) × 壓縮量 (mm)
- 40ShoreA 和 70ShoreA 可訂製
- 工作溫度 = - 40°C ~ 80°C

