



本體			華司·螺絲	
材質	硬度	顏色	材質	處理
NR(橡膠)	55±5 Shore A	黑	鋼	鍍鋅

品號	D	L	d	定數 (N/mm)	最大壓縮量 (mm)	最大荷重 (N)	質量 (g)	庫存
FVC-412301	8	8	M3	43	2	85	1	•
FVC-412321	10	10	M4	40	2.5	100	2	•
FVC-412326		15		27	3.75		3	•
FVC-412331	15	10		163	2	325	4	•
FVC-412341		15	75	3.75	280	6	•	
FVC-412346		20	47	5	234	8	•	
FVC-412351	20	15	M6	151	1.5	227	13	•
FVC-412361		20		86	5	430	16	•
FVC-412371		25		69	6.25	433	19	•
FVC-412381	25	20		124	5	620	26	•
FVC-412386		25		85	6.25	529	29	•
FVC-412391		30	70	7.5	524	25	•	
FVC-412401	30	20	M8	1524	0.7	1067	39	•
FVC-412421		30		141	7.5	1055	45	•
FVC-412431		40		210		2100	53	•
FVC-412441	40	30		1574	80	•		
FVC-412461		40	140	10	1397	98	•	
FVC-412463		50	30	440	7.5	3300	125	•
FVC-412466	40		213	10	2130	150	•	
FVC-412469	50		194	11.25	2188	125	•	
FVC-412471	60	30	M10	556	7.5	4170	189	•
FVC-412476		40		361	10	3610	220	•
FVC-412481		70		624	11.25	7130	335	•
FVC-412501	75	40	M12	697	10	6970	360	•
FVC-412521		55		546	13.75	7510	445	•
FVC-412541	100	40	M16	2000	10	20000	690	•
FVC-412551		55		951	13.75	13080	765	•
FVC-412561		60		753	15	11290	885	•
FVC-412581		75		541	18.75	9640	965	•

Sp. 特長

- 用在減震和降低機件的晃動及噪音

Ps. 備註

- $1N=0.101972\text{kgf}$
- 荷重 (N) = 定數 (N/mm) × 壓縮量 (mm)
- 40ShoreA 和 70ShoreA 可訂製

 訂貨： 交期：

FVC-412301