



材質	處理
SUS630	析出硬化

品號	d ₁ H11	公稱尺寸	d ₂	d ₃ -0.2	d ₄ +0.3	l ₁	l ₂	WS	x ¹⁾	負載荷重 ¹⁾			鎖附扭力 max. (Nm)	搭配 定位扣件	質量 (g)	庫存
										F ₁	F ₂	F ₃				
22350.0900	8	10	M16×1.5	24	9.8	27.5	20	19	1.5	1.2	0.5	90	22350.0601/.0701	34	△	
22350.0902		15											22350.0602/.0702	34	△	
22350.0904		25	M16			37.5	25					75	22350.0604/.0704	47	△	
22350.0906		35				47.5	35					57	22350.0606/.0706	57	△	
22350.0910	10	15	M20×1.5	28	12.2	35.5	24	24	2.7	2.4	2.1	145	22350.0621/.0721	71	△	
22350.0912		25											22350.0623/.0723	74	△	
22350.0914		35	M20			46.0	29					130	22350.0625/.0725	94	△	
22350.0916		50				65.0	49					117	22350.0627/.0727	117	△	
22350.0920	12	15	M24×1.5	32	14.7	35.5	24	27	3.5	3.2	2.8	220	22350.0631/.0731	95	△	
22350.0922		25											22350.0633/.0733	103	△	
22350.0924		35	M24			48.5	36					200	22350.0635/.0735	120	△	
22350.0926		50				72.5	60					164	22350.0637/.0737	164	△	
22350.0930	16	25	M30×2	39	19.2	44.0	29	30	4.8	4.5	4.1	440	22350.0641/.0741	164	△	
22350.0934		50											M30	66.0	44	400
22350.0936		75	96.0			74	325					22350.0645/.0745		325	△	
22350.0954		50	M36×2			70.0	55					348	22350.0673/.0773	348	△	
22350.0956	75	95.0		80	470	22350.0675/.0775	470	△								

· ¹⁾5倍安全係數

Ps. 備註

- 和定位扣件 22350 配合使用
- 確保安全公差和功能
- 可使用在薄版工件
- 耐蝕耐震
- 安全係數 5 倍

訂貨： 交期：
22350.0900

Ex. 使用例

