

RoHS SUS




圖 1 公牙




圖 2 公牙




圖 3 母牙




圖 4 母牙

名稱	材質	顏色
本體	SUS303	-
襯墊	PEEK	藍
螺紋襯套	SUS	-
螺紋銷	SUS	-


品號	型式	h ±0.1	d1	d2	d3	l	t	ws1	ws2	靜態負載 KN max.	鎖附扭力 max.Nm	溫度(°C)		質量 g	庫存
												min.	max.		
22691.0122	圖 1 公牙	15	M8	17	19	8	-	17	4	8.5	10	-60	250	12	△
22691.0133		20	M10	19	21.5	10 ±1		19	5	9.5				21	△
22691.0143		20	M12	22	25	14		22	6	14				32	△
22691.0021	圖 2 公牙	10	M8	12.5	19.4	10	-	17	-	11.5	18	-60	250	14	△
22691.0031		15	M10	14.5	21.9	12		19	-	15.5	32			20	△
22691.0032		15	M10	14.5	21.9	12		19	-	15.5	32			32	△
22691.0041		10	M12	17.5	25.2	14		22	-	22.5	60			28	△
22691.0042	15	M12	17.5	25.2	14	14	22	-	22.5	60	45	△			
22691.0222	圖 3 母牙	15	M8	17	19	-	9	17	-	8.5	10	-60	250	6.3	△
22691.0233		20	M10	19	21.5		10	19	-	9.5				21	△
22691.0243		20	M12	22	25		12	22	-	14				13	△
22691.0324	圖 4 母牙	25	M8	12.5	19.4	-	12	17	-	11.5	18 ¹⁾	-60	250	35	△
22691.0335		30	M10	14.5	21.9		15	19	-	15.5	32 ¹⁾			53	△
22691.0345		30	M12	17.5	25.2		18	22	-	22.5	60 ¹⁾			68	△
22691.0345		30	M12	17.5	25.2		18	22	-	22.5	60 ¹⁾			68	△

· 1) 螺紋需被完全鎖附

SP 特長

- 帶有塑膠表面的支撐座可做保護性的支撐
- 保護接觸面不被損傷

EX 使用例



訂貨： 交期：

22691.0122