

材質	硬度	長度
SUJ2	HRC 58-62	50



PG-9040N
塞規(組)

品號	尺寸範圍 D	支數 組	間隔	精度	庫存
PG-9021N	10.01-10.50	50	0.01	±0.004	△
PG-9022N	10.51-11.00				△
PG-9023N	11.01-11.50				△
PG-9024N	11.51-12.00				△
PG-9025N	12.01-12.50				△
PG-9026N	12.51-13.00				△
PG-9027N	13.01-13.50				△
PG-9028N	13.51-14.00				△
PG-9029N	14.01-14.50				△
PG-9030N	14.51-15.00				△
PG-9031N	15.01-15.50				△
PG-9032N	15.51-16.00				△
PG-9033N	16.01-16.50				△
PG-9034N	16.51-17.00				△
PG-9035N	17.01-17.50				△
PG-9036N	17.51-18.00				△
PG-9037N	18.01-18.50				△
PG-9038N	18.51-19.00				△
PG-9039N	19.01-19.50				△
PG-9040N	19.51-20.00				△

訂貨： 交期：

PG-9021N

Sp 特長

- 可量測孔徑、槽寬、孔心距離和位置、內外傾斜角測定、螺紋和齒輪應用測定等

Wa 注意

- 單支均附塑膠盒包裝，特殊規格及精度等要求可訂製
- 精度檢驗報告需求付費提供