


Type	材質	硬度	長度
PG-9□H	工具鋼	HRC 58-62	40、50
PG-9□T	錫鋼	HRC 78	



PG-9□H · PG-9□T
塞規(組)

品號	尺寸範圍 D	支數 組	間隔	精度	庫存
PG-9000H	0.10- 0.20	11	0.01	±0.001	△
PG-9001H	0.21- 0.50	30			△
PG-9002H	0.51- 1.00	50			△
PG-9003H	1.01- 1.50				△
PG-9004H	1.51- 2.00				△
PG-9005H	2.01- 2.50				△
PG-9006H	2.51- 3.00				△
PG-9007H	3.01- 3.50				△
PG-9008H	3.51- 4.00				△
PG-9009H	4.01- 4.50				△
PG-9010H	4.51- 5.00				△
PG-9011H	5.01- 5.50				△
PG-9012H	5.51- 6.00				△
PG-9013H	6.01- 6.50				△
PG-9014H	6.51- 7.00				△
PG-9015H	7.01- 7.50				△
PG-9016H	7.51- 8.00				△
PG-9017H	8.01- 8.50				△
PG-9018H	8.51- 9.00				△
PG-9019H	9.01- 9.50				△
PG-9020H	9.51-10.00		△		

品號	尺寸範圍 D	支數 組	間隔	精度	庫存
PG-9000T	0.10- 0.20	11	0.01	±0.001	△
PG-9001T	0.21- 0.50	30			△
PG-9002T	0.51- 1.00	50			△
PG-9003T	1.01- 1.50				△
PG-9004T	1.51- 2.00				△
PG-9005T	2.01- 2.50				△
PG-9006T	2.51- 3.00				△
PG-9007T	3.01- 3.50				△
PG-9008T	3.51- 4.00				△
PG-9009T	4.01- 4.50				△
PG-9010T	4.51- 5.00				△
PG-9011T	5.01- 5.50				△
PG-9012T	5.51- 6.00				△
PG-9013T	6.01- 6.50				△
PG-9014T	6.51- 7.00				△
PG-9015T	7.01- 7.50				△
PG-9016T	7.51- 8.00				△
PG-9017T	8.01- 8.50				△
PG-9018T	8.51- 9.00				△
PG-9019T	9.01- 9.50				△
PG-9020T	9.51-10.00		△		

Sp. 特長

- 可量測孔徑、槽寬、孔心距離和位置、內外傾斜角測定、螺紋和齒輪應用測定等

訂貨： 交期：
PG-9000H

Wa. 注意

- 單支均附塑膠盒包裝，特殊規格及精度等要求可訂製
- 以上規格之塞規均附單一塑膠盒及整組包裝
- 精度檢驗報告需求付費提供
- 尺寸公差：±0.001mm
- 表面粗糙度Ra：0.2μm
- 真圓度：0.8μm
- 真直度：1.5μm(2~10mm)